

Sewing Pattern — Skirt 5832

Recommendations on fabric: natural or mixed well draping fabrics

You will also need: blind zipper; lining; elastic tape of 0.5 cm wide or elastic yarn.

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: all seams - 1 cm, hem of the garment and of lining – 2 cm.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Main fabric:

1. Back part - 2 details
2. Front part – 1 folded detail

Lining:

1. Back part - 2 details
2. Front part – 1 detail

INSTRUCTIONS:

1. Serge central edges of back part. Sew center edge of back part from marker downwards. Press seam apart, pressing seam allowance for zipper.
2. Lay zipper under the seam allowance so that zipper blade can not be seen and stitch.
3. Stitch loosely along front part neckline edge. Tie up the neckline to needed length.
4. Sew and serge side and shoulder edges of the dress. Press shoulder and side seams onto back part.
5. Topstitch elastic tape of needed length or put the stitch with elastic yarn on wrong side of front part along the marked line.

6. Sew darts on details of lining, press depths towards center on back part , on front part – upwards. Sew shoulder and side edges of lining, center edge of back part from marker downwards, press seams apart. Join lining and garment right sides touching and overstretch front part and back part neckline edge. Overstretch armhole in two steps: first - upper edge of the armhole, then - lower edge of the armhole. Topstitch seam allowance onto lining by 0, 2 cm off the seam. Turn lining onto wrong side and press. Stitch seam allowance of lining back part center seam to zipper tape.
7. Press seam allowance of dress hem and of lining onto wrong side, turn inside and topstitch.

TECHNICAL DRAWING:

