

Sewing Pattern — Skirt 5828

Recommendations on fabric: natural or mixed, well-draping fabrics

You will also need: lining; fusible interfacing; invisible zipper

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam allowance: all seams – 1cm

Attention! First of all, please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches. They must match up with corresponding pieces.

CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Darts: The fold of the dart is always pressed toward the center of your garment, or down toward the hem.

Main fabric:

1. Back - cut 1
2. Front - cut 1
3. Back waistband/facing - cut 2
4. Front waistband/facing - cut 2
5. Back band- cut 1
6. Front band - cut 1

Lining:

1. Back - cut 1
2. Front -excluding pleats - cut 1

Interfacing: Back facing - cut 1, Front facing - cut 1



INSTRUCTIONS:

1. Apply interfacing to inner facings of the skirt.
2. Sew darts on back, press toward center.
3. Make and baste pleats on front.
4. Sew back waistband to back, and front waistband to front. Press seam allowance toward waistband.
5. Serge seam allowances of left side edges separately. Sew left side seam from zipper notch to bottom edge of garment. Press seam open. Sew in the zipper.
6. Sew right side seam of the skirt. Serge and press seam toward back.
7. Sew front and back side seams of bands together, press seams open. Press band in half lengthwise, wrong sides together. Sew outer edge of band to lower edge of the skirt, press seam toward band. Turn unsewn edge of inner edge of band under, and topstitch into band/skirt connecting seam.
8. Sew lining to facings, serge and press seam allowances upwards. Sew right side edge, serge and press seam toward back. Serge left side edges separately. Sew seam from zipper mark to lower edge of garment. Press seam open.. Serge lower edge of lining, press onto wrong side and topstitch.
9. Pin skirt to lining, right sides together, and sew along top edge of the facing. Understitch, turn facing to inside, and press. Topstitch inner facing into connecting seam of outer waistband and press. Slip-stitch seam allowance of lining to zipper tape.

TECHNICAL DRAWING:

