

Sewing Pattern — Skirt 5825

Recommendations on fabric: denim.

You will also need: fusing, zipper.

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: all seams – 1 cm.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Front part – 2 details
2. Back part – 1 detail
3. Placket along the edge – 2 details
4. Back facing – 2 details
5. Front facing – 4 details
6. Button catch – 1 detail
7. Fly-piece – 1 detail

Fusing:

1. Back facing – 1 detail, front facing – 2 details

INSTRUCTIONS:

1. Apply fusing to back and front facings.
2. Stitch loosely along top and lower edge of back part and gather ruffles. Stitch the facing to top edge of back part.
3. Stitch loosely along top and lower edge of front part and gather ruffles. Stitch the facing to top edge of front part.
4. Sew side seams of the skirt. Serge and press on back part. Sew side seams inner of the facings. Serge lower edge.
5. Stitch fly-piece to right part of front part. Serge center edge of front part and fly-piece. Sew center seam of front part up to the zipper notch.
6. Press the fly-piece onto wrong side. Stitch zipper under the edge of zipper allowance into the edge. Stitch free zipper tape onto right half to the fly-piece, without catching fabric of front half.

Fold button catch in half lengthwise and overstitch short lower and upper edges. Turn button catch out, press and serge together straight vertical edges. Topstitch zipper seam allowance onto zipper and onto button catch on left half of the skirt.

7. Cut right front part facings to the fly-piece length. Serge outer edge of fused facing of front and back parts. Overstitch upper edge of front and back part's facing of the skirt with fused facing. Turn inside middle edge of facing and put decorative stitch on right side of front part, catching the fly-piece and turned middle edge (of the right side) of the facing, turn middle edge (of the left side) of the belt inside and topstitch into button catch connecting seam.

8. Put decorative stitches along side seams, facings, center edge of front parts.

9. Sew edge of the placket along the edge. Fold details of the placket right sides together and sew. Turn onto right side and press. Serge inner edge of the placket. Stitch placket to hem of the skirt, distributing the ruffle evenly. Fasten inner placket with decorative stitch on right side. Put decorative stitch along the edge of the skirt.

TECHNICAL DRAWING:

