

## Sewing Pattern — Tunic 5823

Recommendations on fabric: natural or mixed knitted fabric of low or medium stretchiness

You will also need: bias tape

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Seam allowance: along the lower edge of back part and of front part – 1.5 cm; along neckline of back part and shaped edge of the armhole of back part – 1.5 cm; other seam allowances – 0.7 cm

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



### **CUTTING:**

Main fabric:

1. Back part – 1 detail
2. Front part – 1 folded detail
3. Yoke – 2 details

Advice:

Knitted fabric details are sewn together with special elastic or narrow zig-zag stitch. When serging cut seam allowances to 0.6 – 0.8 cm. Seam allowance on turnup is stitched with twin needles to save stretchiness. Details also can be sewn together via 3 or 4 – threaded serger.

### **INSTRUCTIONS:**

1. Overstitch yoke along neckline and armhole edges, turn onto right side, press.
2. Make pleats according to markers and fasten. Fold bias tape in half lengthwise wrong sides together and press. Fold the bias tape with the edge of the armhole of front part, from right side and overstitch, turn the bias tape onto wrong side and topstitch along the fold onto main detail.
3. Stitch yoke to front part, press seam allowances onto yoke and serge.
4. Press seam allowances onto neckline and back part armhole turnup. Turn seam allowances away. Sew shoulder seams, press seam onto back part and serge.
5. Serge back part neckline edge and shaped edges of the armhole, slash the edge of the armhole in corner, press onto wrong side and topstitch.

6. Sew side seams, press seam onto back part and serge.
7. Serge hem of the garment, press onto wrong side and topstitch.

**TECHNICAL DRAWING:**

