

Sewing Pattern — Top 5815

Recommendations on fabric: thin blouse fabric (silk, viscose, polyester)

You will also need: elastic yarn; bias tape of the same color as the top (approximate length is mentioned on front part pattern)

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: hem of the garment – 2 cm, along back part / front part neckline and armholes edges – 0 cm, other seams - 1cm

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Main fabric:

1. Back part - 1 detail
2. Front part - 1 detail

INSTRUCTIONS:

1. Make a slit on back part and overstretch it with bias tape.
2. Stitch loosely along front part neckline edge and gather ruffles between notches.
3. Sew shoulder seams, press seam onto back part and serge.
4. Overstretch neckline edge with bias tape, sewing ties on back part at the same time. Overstretch edges of armholes.
5. Sew side seams. Press seam allowances towards back part and serge.
6. Serge hem of the garment, press onto wrong side and topstitch.
7. Put stitches with elastic yarn according to marking.

TECHNICAL DRAWING:

