

Sewing Pattern — Dress 5813

Recommendations on fabric: natural or mixed thin dress fabric

You will also need: blind zipper, fusing

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: all seams - 1 cm, hem of the garment - 3 cm, hem of sleeve - 2.5 cm

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Main fabric:

1. Central part of the back – 2 details
2. Middle part of the back – 2 details
3. Central part of the front – 2 details
4. Middle part of the front – 1 detail
5. Back part of the skirt – 2 details
6. Front part of the skirt – 1 detail
7. Facing of the back – 2 details
8. Facing of the front – 1 detail

Fusing: facings of the back part, facing of the front

INSTRUCTIONS:

1. Apply fusing to details of the facings.
2. Sew waist darts on panels of the skirt. Press depths of the darts towards center of detail.
3. Lay facings of the front onto central part of the front right sides together and overstretch center edge from marker upwards and the front's neckline, leaving 3 - 4 cm to shoulder edges. Sew center edge of central part of the front and center edge of front's facing. Press apart the seam. Slash seam allowances on rounded parts, cut in corners, turn the facing onto wrong side, serge, press.
4. Stitch loosely along lower edges of central parts of the back and of the front and gather ruffle.

5. Stitch central part of the front to middle part, without catching lower part of the facing, press seam allowances downwards and serge. Stitch front skirt part to middle part, press seam allowances upwards and serge.
6. Stitch central part of the back to middle part, press seam allowances downwards and serge. Stitch back skirt part to middle part, press seam allowances upwards and serge.
7. Serge center edge of the back and vent sides. Sew in zipper. Turn lower part of zipper aside and sew center edge of the back and upper edge of the vent. Sew the seam from «zipper» notch and downwards. Slash seam at the vent's beginning. Press center edge apart, press the vent onto left part of the back. Put decorative stitch along top edge of the vent.
8. Sew shoulder seams of the dress, press seam allowances towards the back and serge. Sew shoulder seams of the facings, press seam allowances apart. Serge outer edge of the facing.
9. Fold the facing with main fabric details right sided touching and overstretch unsewn neckline edge of the front and the neckline of the back. Slash seam allowances on rounded parts, turn the facing onto wrong side and press. Turn short edges of the back's facing inside and tack to zipper tape. Topstitch the facing onto the back and onto the front along outer edge.
10. Press sleeve hem seam allowance onto wrong side, turn inside and topstitch.
11. Sew side seams. Press seam allowances towards the back and serge.
12. Serge hem of the garment, press onto wrong side and topstitch.

TECHNICAL DRAWING:

