

Sewing Pattern — Blouse 5807

Recommendations on fabric: middle/high stretchable jersey (natural or mixed).

You will also need: fusing.

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: 0.7 cm for the front and back neckline edge, 1.5 cm for the seam allowance from the shoulder edge to the notch at the front and back parts, 1 cm for other seams.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Back part – 1 piece folded in the middle
2. Front part – 1 piece folded in the middle
3. Placket – 1 piece
4. Back neckline facing – 1 piece
5. Front neckline facing – 1 piece
6. Belt loop – 1 piece

Fusing:

1. Back neckline facing – 1 piece
2. Front neckline facing – 1 piece

OUR ADVICE: stitch jersey details with special elastic/zig-zag stitches. Topstitch hem allowances with double needle or using a flatlock machine to save elasticity. You can also use a 3- or 4-thread overlock to stitch the details.

INSTRUCTIONS:

1. Apply fusing to the wrong side of front and back neckline facing.
2. Stitch front and back shoulder edges. Serge seam allowances and press them to the back.
3. Stitch front and back neckline facings into a ring. Press seam allowances and serge them, serge the outer edge. Put the facing and the garment together wrong side out and pipe the neckline

edge. Press seam allowances, slash them at rounded edges, turn the facing out onto the wrong side and topstitch at 1 cm from the neckline edge.

4. Slash seam allowances at the notch on the side front and back edges. Stitch the side front and back edges together starting at the notch and down. Serge seam allowances and press them onto the back.

5. Serge the open side front and back edges, press them onto the wrong side and topstitch.

6. Stitch the placket piece into a ring, fold it lengthwise in half wrong side out and stitch to the garment hem. The placket stitch is at the left side stitch of the garment. Press and serge seam allowances.

7. Fold the belt loop lengthwise in half wrong side out and pipe it at 0.5-0.7 cm from the longer edge. Turn it out to the right side, neaten the seam, arranging it on the fold and press. Cut belt loops of the required size and topstitch them according to the marks. Put in a leather belt 2 cm wide.

TECHNICAL DRAWING:

