

Sewing Pattern — Blouse 4253

Recommendations on fabric: silk stretch - atlas.

You will also need: fusing; 2 buttons.

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Seam allowance: all seams - 1 cm.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Main fabric:

1. Back part - 1 folded detail
2. Front part - 1 folded detail
3. Front part inset - 1 detail
4. Top basque of front part - 1 folded detail
5. Lower basque of front part - 1 folded detail
6. Back part inset - 1 detail
7. Top basque of back part - 1 folded detail
8. Lower basque of back part - 1 folded detail
9. Belt – 2 details (or 1 folded detail)
10. Sleeve – 2 details
11. Cuff – 2 details
12. Front neckline facing – 1 detail
13. Back neckline facing – 1 detail

Fusing:

1. Cuff – 2 details
2. Front neckline facing – 1 detail
3. Back neckline facing – 1 detail

INSTRUCTIONS:

1. Apply fusing to details.
2. Make soft pleats on back part and front part details, depths of pleats are turned towards shoulder seam. Fix pleats along neckline edges.
3. Sew shoulder and side seams. Serge and press seam allowances to back part.
4. Sew, serge and press shoulder edges of the facings to back part. Serge outer edge of the facings. Fold facings with main detail right sides together and overstretch neckline edge. Slash seam allowances, turn facings out and press.
5. Sew separately side edges of insets, top and lower basques. Press seam allowances to back part and serge. Serge lower edges of basques, turn inside at 1 cm and topstitch.
6. Stitch inset to main detail. Press seam allowances onto inset and serge. Lay basques one onto another and fix along top edge. Stitch basques to inset, press seam allowances onto inset and serge.
7. Slash the slit of sleeve according to the notch. Cut bias tape of 4 cm wide and as long as double slit length + 3 cm. Press bias tape in half lengthwise, turn inside outer edges towards center and press again. Overstretch the slit with bias tape. Cut extra tape off. Sew edge of sleeve, serge and press. Stitch loosely along lower edge of sleeve and gather ruffles. Fold cuff in half lengthwise right sides together and sew side edges and overstretch the corner. Start and finish the stitch exactly near marked line of cuff connecting seam. Turn detail onto right side, press. Stitch outer side of cuff to the sleeve, turn inside seam allowance of inner side of cuff and topstitch into outer cuff connecting seam. Stitch loosely along top part of rounded part and gather ruffles. Sew sleeve into armhole, leveling notches. Serge and press seam allowances to the sleeve.
8. Make buttonholes and sew buttons on cuffs.
9. Sew details of the belt. Press seam allowance apart. Fold belt in half lengthwise right sides together and overstretch short and long side, leaving a slit of 10-15 cm on long side. Turn belt out, straighten and press. Sew the slit.

TECHNICAL DRAWING:

