

Sewing Pattern — Lingerie 5784

Recommendations on fabric: thin fabric.

You will also need: decorative elastic trim in contrasting color, thread in contrasting color for decoration, ready straps in contrasting color, trim.

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Seam allowance 1 cm on all edges, seam allowance on hem – 0 cm. Seam allowance of the armhole of front part and upper edge of back part and of front part — 2.5 cm.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Main fabric:

1. Back part – 1 detail
2. Front part— 1 detail

INSTRUCTIONS:

1. Sew side seams. Press towards back part and serge.
2. Overstitch top and lower edges with thick thin rolled seam, using threads in contrasting color.
3. Cut two pieces of elastic trim – one part equals overbust measurement, the other one equals underbust measurement.
4. Mark lines for topstitching elastic trim along the top edge and under bust. Topstitch trim onto garment, stretching it and distributing ruffles evenly.
5. Sew on straps. Optionally you may make a bow from decorative trim and sew it on according to the picture.

TECHNICAL DRAWING:

