

Sewing Pattern — Nightdress 5780

Recommendations on fabric: chiffon

You will also need: decorative tape

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Seam allowances: all seams - 1 cm.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Back part – 1 detail
2. Front part – 1 detail
3. Cup – 2 details

INSTRUCTIONS:

1. Sew darts on cups, cut depth of darts up to 0.5 cm and serge. Sew cups into front part detail, serge.
2. Sew side seams, press seam onto back part and serge.
3. Serge upper and lower edges.
4. Cut bias tape from main fabric, width is 4 cm and length is equal to length of lower part of the armhole. Press bias tape in half lengthwise, wrong sides together. Fold bias tape with lower part of the armhole right sides touching and overstretch. Turn the bias tape onto wrong side. Topstitch seam allowance onto the bias tape with 0.1 cm seam.
5. Cut decoration for top edge from main fabric, width is 8 cm (approximate length is mentioned on detail of back part). Overstretch all sides with rolled seam, stretch loosely in the center and tie up up to needed length (approximate length is mentioned on detail of back part). Topstitch decorative tape onto decoration and topstitch decoration onto back part and front part neckline edge, shaping straps.
6. Cut decoration for lower edge from main fabric, width is 8 cm (approximate length is mentioned on detail of back part). Sew detail into ring, press seam apart and serge. Overstretch long sides with rolled seam, stretch loosely in the center and tie up to the length lower edge. Topstitch tape onto decoration and topstitch decoration onto hem of garment.

TECHNICAL DRAWING:

