

Sewing Pattern — Tunic 5771

Recommendations on fabric: natural/mixed fabric (cotton, viscose, polyether)

You will also need: piping

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Seam allowances: 1.5 cm for the hem, 0 cm for front/back necklines, 1 cm for other seams

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Back part – 1 piece
2. Front part – 1 piece
3. Back sleeve – 2 pieces
4. Front sleeve – 2 pieces

INSTRUCTIONS:

1. Stitch front darts. Press darts upward. Stitch back darts. Press darts toward back center.
2. Trim front/back vertical stitches between side mark and the hem: fold allowances into wrong side twice, then topstitch.
3. Stitch side seams between armholes and notches. Stitch right shoulder seam. Neaten seams and press them backward. Neaten the neckline with the piping. Stitch left shoulder seam. Neaten the seam and press it backward.
4. Stitch sleeve edges between sleeve cap and the notch. Neaten seams and press them apart. Topstitch the segment between the notch and the hem. Stitch sleeve into armholes easing them along sleeve caps.
5. Fold the hem twice and topstitch it.

TECHNICAL DRAWING:

