

Sewing Pattern — Blouse 5769

Recommendations on fabric: natural/mixed fabric (cotton, viscose, pleather)

You will also need: fusible interfacing; separating zipper; 2 buttons

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam allowance: 1.5 cm for the hem, 1 for other seams

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches, they must match up with corresponding pieces.



CUTTING:

(On the pattern pieces, “beam” means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.)

Darts: The fold of the dart is always pressed toward the center of your garment, or down toward the hem.

Main fabric:

1. Back – cut 2
2. Center front – cut 4
3. Side front – cut 2
4. Sleeve – cut 2
5. Cuff – cut 2
6. Front facing – cut 2
7. Back facing_1 – cut 2
8. Back facing_2 – cut 2

Interfacing:

1. Cuff – cut 2
2. Front facing - cut 2
3. Back facing_1 – cut 2

4. Back facing_2 – cut 2
5. Center front – cut 2

INSTRUCTIONS:

1. Apply the interfacing to wrong side of center front, facings and cuffs.
2. Lay each pair of center fronts, right sides together, with one side of the zipper in between (zipper teeth are facing the inside). Sew front edges together, close to teeth. Turn right side out and press. Topstitch along each side of zipper at 0.7 cm from seams. Sew front sides to center fronts. Trim seams and press toward side.
3. Sew back darts. Press darts toward center. Stitch center back seam, serge and press toward left.
4. Sew shoulder/side seams. Serge seams and press toward back.
5. Sew facings together. Serge seams and press, serge outer edge. Sew facings to upper edge, right sides together, catching a segment of front side seam. Turn the facing to wrong side and topstitch at 0.7 cm.
6. Sew sleeve seam up to the notch, serge and press. Sew a gathering stitch along cap of sleeve for ease. Sew sleeves into armholes matching marks and easing around sleeve caps.
7. Fold cuffs, right sides together, and sew short sides to notch. Trim seam allowance close to the notch. Turn cuffs right side out and press them. Stitch outer cuff to the sleeve. Fold inner cuff seam allowance under, and topstitch along joining seam.
8. Serge hem edge, press under, and topstitch.
9. Make buttonholes on cuffs and sew buttons.

TECHNICAL DRAWING:

