

## Sewing Pattern — Blouse with Elastic Braid 5765

Recommendations on fabric: sheer natural/mixed fabric (cotton, viscose, polyether).

You will also need: elastic; decorative braid.

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: 2 cm for garment/sleeve hems, 1 cm for other seams.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



### **CUTTING:**

Fabric:

1. Back part – 1 piece
2. Front part – 1 piece
3. Sleeve – 2 pieces

### **INSTRUCTIONS:**

1. Stitch right shoulder seam. Neaten it and press it backward. Make a seam with loose stitches along the neckline and gather the neckline a little. Fold neckline allowance into wrong side and stitch the braid on it. Stitch left shoulder seam. Neaten the seam and press it backward. Stitch side seams. Neaten the seams and press them backward.
2. Stitch sleeve edges. Neaten seams and press them. Stitch sleeves easing them at sleeve caps.
3. Neaten garment/sleeve hems, fold them under and topstitch excluding a hole for the elastic. Pull the elastic into garment/sleeve hems.

**TECHNICAL DRAWING:**

