

Sewing Pattern — Blouse 5754

Recommended fabric: natural/mixed fabric.

You will also need: fusible interfacing; 2 eyelets; 4 buttons.

If the pattern has a double line around it, the seam allowances are included.

Seam allowance: 1 cm for all seams, 2 cm for the hem.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches, they must match up with corresponding pieces.

CUTTING:

(The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.)

Darts: The fold of the dart is always pressed toward the center of your garment, or down toward the hem.

Main fabric:

1. Back – cut 2
2. Front –cut 2
3. Sleeve – cut 2
4. Collar – cut 2
5. Collar-stand – cut 2
6. Placket – cut 2
7. Cuff –cut 2
8. Scarf – cut 1

Fusible interfacing: plackets, outer collar, outer collar stand, cuffs.

INSTRUCTIONS:

1. Apply the interfacing to wrong side of plackets, outer collar, collar-stand, cuffs.
2. Sew back/front darts. Press toward center. Sew back center seam. Serge and press seam toward left.



3. Pin collar, right sides together, and sew outer edges. Trim corners, then turn collar right side out. Sew collar-stand together inserting the ready collar: begin and finish stitching at the line joining the collar-stand. Turn right side out, press.
4. Pin placket to front, right sides together, and sew along front edge. Trim seam allowance, turn the placket onto wrong side, and press. Fold free long edge of the placket under and topstitch from front. Set eyelets as marked.
5. Sew shoulder/side edges. Serge and press seams toward back.
6. Sew inner collar-stand with the collar into the neckline, fold outer collar-stand seam allowance under, and topstitch along the seam joining the inner collar-stand. Topstitch along the collar.
7. Serge bottom edge of sleeve. Sew sleeve seam, excluding a segment between the mark and the hem.
8. Fold cuffs, right sides together, and sew side seams, trim corners and turn right side out. Press cuffs. Sew cuff's outer side to sleeve edge. Fold inner cuff's seam allowances under, and topstitch along joining seam.
9. Make a gathering stitch along sleeve cap for ease. Sew sleeves into armholes, matching marks, and easing along sleeve caps. Serge seams.
10. Press bottom edge of garment onto wrong side, fold edge under, and topstitch. Make buttonholes into the cuffs and sew buttons.
11. Fold the scarf along the center, right sides together, and sew along three edges leaving an opening for turning. Turn scarf right side out, and topstitch at 0.1 cm from the edge.

TECHNICAL DRAWING:

