

Sewing Pattern — Skirt 5752

Recommendations on fabric: natural/mixed fabric.

You will also need: fusing; blind zipper.

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: 1 cm for all seams.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Center part – 2 pieces
2. Side part – 4 pieces
3. Yoke – 4 pieces
4. Flounce – 2 pieces

Fusing:

1. Yoke – 2 pieces

INSTRUCTIONS:

1. Apply the fusing to wrong side of the yoke.
2. Stitch center part to side part. Neaten seams and press them toward the center.
3. Stitch straightened yoke to the skirt. Neaten seams and press them upward.
4. Stitch skirt right seam and neaten it. Press the seam backward. Stitch left side seam between closure mark and the hem pressing closure allowance, then neaten the seam. Lay the zipper under allowances with its teeth hidden.

5. Stitch flounces together. Neaten seams and press them. Stitch the flounce to skirt hem. Neaten the seam and press it upward. Neaten flounce's lower edge, fold it 1 cm under and topstitch. Press the seam.
6. Stitch yokes without fusing along right side seam. Neaten joining sea as well as open side edges and yokes' lower edges. Presseams. Lay the skirt and inner yokes right sides together and overstretch them along upper edge. Topstitch the overstretching on inner yoke at 0.2 cm from the seam.
- Fold inner yokes into wrong side and press them. Stitch side open edges to zipper allowances. Topstitch inner yokes along the seam joining outer yokes, then press.

TECHNICAL DRAWING:

