

Sewing Pattern — Raincoat 5749

Recommendations on fabric: soft fabric suitable for rain coats/bonded fabric

You will also need: separating zipper; bias strip 4 cm x length of coat

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam allowance: 0 cm for collar edge; 1 cm for other seams

Attention! First of all, please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches. They must match up with corresponding pieces.



CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Darts: The fold of the dart is always pressed toward the center of your garment, or down toward the hem.

Fabric:

1. Back – cut 2
2. Front – cut 2
3. Sleeve – cut 2
4. Cuff – cut 2

INSTRUCTIONS:

1. As a design element, darts are sewn with their seams ‘right side’ out on front and back. Trim dart edges to 0.7 cm.
2. Sew center back, shoulder, and side seams. Trim seams to 0.7 cm.
3. Sew sleeve seams. Trim allowances to 0.7 cm. Sew cuffs into a ring. Trim seam allowances to 0.7 cm. Stitch cuffs to sleeves. Leave cuffs’ turned up edge raw.
4. Make a gathering stitch along sleeve cap for ease. As a design element, sew sleeves into armholes easing along sleeve caps with sleeves’ seams on ‘right side’. Trim seam allowances to 0.7 cm.

5. Pin zipper on right side of fabric with zipper teeth facing toward side, baste in place. Fold bias tape in half lengthwise and press. Pin raw edges of bias tape over zipper tape and front edge, then sew. Turn bias tape onto wrong side, press and topstitch.
6. Leave coat's hem raw.

TECHNICAL DRAWING:

