

Sewing Pattern — Skirt 5744

Recommendations on fabric: natural or mixed fabric

You will also need: fusible interfacing; zipper

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam allowance: 1 cm for all seams; 3 cm for the hem

Attention! First of all, please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches. They must match up with corresponding pieces.



CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Darts: The fold of the dart is always pressed toward the center of your garment, or down toward the hem.

Fabric:

1. Upper back waistband/facing– cut 2
2. Back yoke – cut 1
3. Back skirt – cut 1
4. Upper front waistband/facing – cut 2
5. Front yoke – cut 1
6. Right front skirt – cut 1
7. Left front skirt – cut 1

Fusible interfacing: 1 upper front waistband, 1 upper back skirt

INSTRUCTIONS:

1. Apply the interfacing to wrong side of upper front waistband and upper back waistband.
2. Sew back waistband to back yoke. Serge and press seam allowances upward.
3. Sew back yoke to back skirt. Serge and press joining seam toward yoke.
4. Sew front waistband to front yoke. Serge and press seam allowances upward.
5. Sew right front skirt to front yoke. Slash seam allowances close to the mark, serge and press toward yoke. Stitch left front skirt to front yoke. Slash seam allowances close to the mark, serge and press seam toward yoke. Stitch free edge of front left/front right skirts. Serge edges separately and press seam allowances apart.
6. Sew skirt's right side seam. Serge edges separately and press seam allowances apart. Make decorative stitch at 0.5 cm from the seam joining upper front/back skirts. Serge left side edges separately. Sew left side seam from zipper mark to hem. Press seam allowances apart and opening for zipper. Sew in zipper.
7. Sew right side seam of waistband facings. Press seam apart. Serge facing lower edge.
8. Pin waistband facing, right sides together, to top edge of waistband and sew upper edge. Understitch and turn onto wrong side. Tack to seams. Fold side edges under and slipstitch to zipper tape. Make a decorative stitch along upper edge at 0.5 cm from the edge.
9. Serge lower edge of garment, press onto wrong side, and topstitch it.

TECHNICAL DRAWING:

