

Sewing Pattern — Blouse 5743

Recommendations on fabric: natural or mixed fabric

You will also need: fusible interfacing; trim (if desired); 7 buttons

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam Allowance: 1 cm for all seams, 1.5 cm for the hem.

Attention! First of all, please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches, they must match up with corresponding pieces.



CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Main fabric:

1. Center back– cut 2
2. Side back – cut 2
3. Back yoke – cut 1
4. Side front– cut 2
5. Middle front – cut 2
6. Center front – cut 2
7. Front yoke – cut 2
8. Collar – cut 2
9. Collar-stand – cut 2
10. Placket – cut 2
11. Sleeve – cut 2
12. Cuff – cut 2

Interfacing: plackets, outer collar, outer collar-stand, cuffs

INSTRUCTIONS:

1. Apply the interfacing to plackets, outer collar, outer collar-stand, cuffs.

2. Sew collars, right sides together. Clip into curves, turn collar right side out. Sew collar stands together inserting the collar. Turn the collar right side out and press.
 3. Sew back sides to center backs, serge seam and press toward center. Sew center back seam. Serge seam and press toward left. Sew back yoke to back, serge seam and press toward the yoke.
 4. Sew side front to middle front. Serge seam and press toward center. Sew middle front to center front. Serge seam and press toward center. Sew the front yoke to front, serge seam and press toward yoke.
 5. Press plackets along the center, wrong sides together. Sew outer placket to center front edge, press seam allowance toward the placket. Fold inner placket's free long edge onto wrong side and topstitch along the seam joining outer placket.
 6. Sew shoulder/side seams. Serge and press seams toward back.
 7. Sew outer collar-stand with the collar into the neckline, fold inner collar-stand seam allowance under, and topstitch along the seam joining the outer collar-stand.
 8. Sew sleeve seam and serge seam allowance. Sew a gathering stitch along the sleeve cap and sleeve bottom edge. Adjust gathering to match length of cuff.
 9. Fold cuff, right sides together, and sew short edges. Clip corner, and turn right side out. Sew outer cuff edge to sleeve edge. Fold inner cuff's seam allowance under and topstitch along the joining seam. Make buttonholes and sew buttons.
 10. Sew sleeves into armholes, matching notches and adjusting ease along cap. Serge seam allowance.
 11. Serge garment lower edge. Turn under, press, and topstitch hem.
 12. Make buttonholes on right placket/collar-stand, sew buttons on left placket/collar-stand.
- *If desired: you can sew trim along seams, as shown in the picture.

TECHNICAL DRAWING:

