

Sewing Pattern — Jacket 5741

Recommendations on fabric: denim

You will also need: fusible interfacing; separating zipper; 6 buttons

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam allowance: 1 cm for all seams, 3 cm for pocket flap upper edge

Attention! First of all, please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches. They must match up with corresponding pieces.



CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Fabric:

1. Center back – cut 1
2. Side back – cut 2
3. Back waistband – cut 1
4. Side front – cut 2
5. Center front– cut 2
6. Front right waistband – cut 1
7. Front left waistband – cut 1
8. Stand-up collar – cut 2
9. Front band facing – cut 2
10. Pocket – cut 2
11. Flap – cut 4
12. Sleeve – cut 2
13. Sleeve inset –cut 2
14. Cuff – cut 2

Fusible interfacing: front band facing, stand-up collar, cuff, back waistband, front right waistband, front left waistband, back neck facing

INSTRUCTIONS:

1. Apply the interfacing to wrong side of front band facing, stand-up collar, cuff, back waistband, front right waistband, front left waistband, back neck facing.
2. Pin stand-up collar right sides together, and sew closure allowance, outer edge and shaped end. Clip into curves, turn the collar right side out and press.
3. Sew side fronts to center fronts, and side backs to center back. Serge and press seams toward center. Make decorative stitch at 0.1 cm from joining seam.
4. Lay front parts right sides together, adjust edges, measure front edge length. Sew the zipper to front edges (teeth face toward sides). Fold front edge allowance at closure segment, then press.
5. Press pocket upper edge onto wrong side, fold it under, then topstitch. Press pocket side and lower edges onto wrong side. Pin pockets on front as marked. Topstitch pockets with double stitches at 0.1 cm and 0.7 cm from edges.
6. Pin flaps right sides together and sew outer edges. Clip into curves and turn right side out. Press seams. Make decorative double stitch at 0.1 cm and 0.7 cm from flap edges. Serge flap free edge. Make a buttonhole. Sew the flap to front, fold it downward and topstitch with double stitch at 0.1 cm and 0.7 cm distance. Sew a button on the pocket according to the buttonhole.
7. Serge front band facing outer edge. Pin the front band facing on front, right sides together and sew along front edge, close to zipper teeth. Turn facing onto wrong side, press. Topstitch center front along zipper.
8. Sew shoulder and side seams. Serge and press seams toward back.
9. Sew outer stand-up collar into the neckline, fold inner lower edge of inner collar under, and topstitch along the joining seam. Make decorative stitch along stand-up collar. Fix front band facing at shoulder seams with 1 cm stitch.
10. Sew front waistbands to back waistband. Press seams apart. Press the waistband along the center right side out. Stitch outer waistband to jacket hem, press joining seam toward the waistband.
11. Sew waistband short sides, right side together. Trim corners, turn right side out. Fold inner waistband open edge under, and topstitch along joining seam. Make decorative stitch along waistband perimeter.
12. Sew sleeve inset to the sleeve leaving slit segment unstitched. Trim seam allowances close to mark, press them toward the inset pressing slit segment. Make decorative double stitch at 0.1 cm and 0.7 cm from the seam.
13. Sew sleeve seam, serge, and press.
14. Fold cuff along the center, right sides together, sew shaped end and closure allowance. Trim corners, turn right side out, and press.
15. Sew outer cuff to sleeve lower edge. Fold inner cuff upper edge under, and topstitch it along joining seam. Make decorative stitch along cuff outer edges.
16. Make a gathering stitch on sleeve cap for ease. Sew sleeves into armholes, matching marks and adjusting ease. Serge and press allowances toward the armhole. Topstitch with double stitch at 0.1 cm and 0.7 cm from the joining seam.
17. Make buttonholes into the collar/waistband/cuffs. Sew button correspondingly.

TECHNICAL DRAWING:

