

Sewing Pattern — Pants 5740

Recommendations on fabric: natural/mixed fabric suitable for pants

You will also need: fusible interfacing; sheer fusing for pant leg hem; zipper; 2 buttons; lining

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam allowance: 1 cm for all seams, 2.5 cm for hems.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches, they must match up with corresponding pieces.



CUTTING:

(On the pattern pieces, “beam” means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.)

Darts: The fold of the dart is always pressed toward the center of your garment, or down toward the hem.

Main fabric:

1. Back – cut 2
2. Front – cut 2
3. Back waistband– cut 2
4. Right front waistband – cut 2
5. Left front waistband– cut 2
6. Zipper fly – cut 1
7. Side front/pocket back – cut 2
8. Belt loop – cut 8
9. Belt – cut 1

Lining:

1. Pocket Bag – cut 2

Fusible interfacing: front left/right inner waistbands, back inner waistband, zipper fly

INSTRUCTIONS:

1. Apply the interfacing to wrong side of front left/right inner waistband, back inner waistband, zipper fly. Apply a 1-cm width strip of interfacing to pocket entrance.
2. Sew side seams of front/back facings. Press seam open.
3. Sew back darts. Press toward center. Serge center back edges separately, sew center back seam and press open.
4. Lay the pocket bag on front, right sides together, and sew to pocket entrance. Fold the pocket bag under, to wrong side, and press. Topstitch along pocket entrance at 0.1 cm and 0.7 cm from pocket entrance, then press. Place side front under front along marks for pocket entrance. Sew the pocket bag. Baste side front to front with 1 cm stitch along upper/side edges.
5. Sew in fly zipper. Here are several easy methods: Illustrations and explanation [Sew in Fly Zipper](#) and [Video: An Easy, Flat Fly-Front Zipper](#). (Note: the zipper fly facing is not used in this method.)
6. Sew side seams, serge or finish seams and press. Sew inside leg seams, serge or finish seams and press.
7. Place 2 belt loops right side together, sew them along outer edges, leaving upper edge unstitched. Turn the belt loop right side out, press and topstitch along the edges. Do the same for other belt loops. Sew belt loops to waistband upper edges as marked.
8. Lay inner and outer waistband, right sides together, and sew upper edges. Turn right side out and press. Understitch seam on inner waistband at 0.2 cm from the seam. Serge or finish inner waistband lower edge. Sew outer waistband to pant's upper edge matching side seams. Sew waistband front edges. Trim corners, turn them right side out and press. Topstitch inner waistband finished edge along joining seam. Topstitch belt loops on waistband lower edges.
9. Serge or finish bottom edge of pant legs. Turn under and press. Hem pants with sheer fusing or as desired. Make buttonholes on right front waistband, sew buttons to left one.
10. Fold the belt along the center, right sides together, and sew short edges and long edge, leaving an opening for turning. Turn the belt right side out, Slipstitch opening closed. Topstitch a double row of stitches at 0.1 cm and 0.7 cm along belt's perimeter.

TECHNICAL DRAWING:

