

Sewing Pattern — Jacket 5739

Recommendations on fabric: natural or mixed suiting fabric

You will also need: fusible interfacing; lining; 5 buttons

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam allowance: 1 cm for all seams, 2 cm for hems, 3 cm for pocket upper edge.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches, they must match up with corresponding pieces.



CUTTING:

(On the pattern pieces, “beam” means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.)

Darts: The fold of the dart is always pressed toward the center of your garment, or down toward the hem.

Fabric:

1. Center back – cut 1
2. Side back – cut 2
3. Back yoke – cut 1
4. Center back waistband (inset) – cut 1
5. Side back waistband (inset) – cut 2
6. Lower back – cut 1
7. Side front – cut 2
8. Center front – cut 2
9. Center front waistband (inset) – cut 2
10. Side front waistband (inset) – cut 2
11. Lower front – cut 2
12. Stand-up collar – cut 2
13. Front facing (band) – cut 2
14. Back neck facing – cut 1
15. Upper sleeve – cut 2

16. Lower sleeve – cut 2
17. Belt – cut 1
18. Pocket – cut 2

Lining:

1. Back waistband (inset) – cut 1
2. Front waistband (inset) – cut 2

Interfacing: front facing, inner stand-up collar, back neck facing, center back waistband, side back waistband, center front waistband, side front waistband.

INSTRUCTIONS:

1. Apply the interfacing to wrong side of front facing, inner stand-up collar, back neck facing, center back waistband, side back waistband, center front waistband, side front waistband.
2. Lay stand-up collars right sides together and sew outside edge, begin and stop stitching at collar joining line. Clip into curves, turn collar right side out and press.
3. Sew side backs to center back and side fronts to fronts. Serge or finish seam and press toward center. Double topstitch at 0.1 and 0.7 cm from joining seams.
4. Press pocket upper edge to wrong side, fold it under and topstitch with double stitches. Press pocket allowances to wrong side, lay the pocket on front part according to marks, and topstitch with double stitches.
5. Sew the yoke to back part. Serge or finish seam and press toward the yoke, make a double topstitch at 0.1 and 0.7 cm from joining seams.
6. Sew side edges of upper front to upper back parts, serge or finish seam and press toward back. Sew side edges of lower back to lower fronts, press, serge or finish seam and press toward back.
7. Sew side back waistbands to center back waistband. Sew side front waistbands to center front waistbands. Press seam toward the center and double topstitch at 0.1 and 0.7 cm from joining seams. Sew side seams of back and front waistband, press seam allowances apart. Make belt holes into the waistband as marked. Sew side edges of lining front/back waistband. Press seam allowances apart. Serge or finish the bottom edge.
8. Lay fabric and lining waistbands, right sides together along upper edge, insert jacket's upper part between them, sew all three together. Turn waistbands downwards. Sew jacket's lower part to fabric waistband making pleats as marked. Press seam allowances toward the waistband. Topstitch lining bottom edge along the seam joining fabric waistband to jacket's lower part. Double topstitch at 0.1 and 0.7 cm from joining seams of the waistband.
9. Sew shoulder seam, serge or finish shoulder seam edges separately and press open.
10. Sew shoulder seam of front facings and back neck facing. Press seam allowances open and finish or serge edges. Serge or finish outer edge of entire facing. Sew outer stand-up collar into jacket neckline. Place facing, right sides together, onto front and inner collar edge, matching seams and marks. Sew facing to front and inner collar. Clip into curves, press. Understitch as far as possible on front facing. Turn to inside and press.
11. Stitch front facing hems to front part as marked. Clip seams in front edge lower corners. Turn front edge out, press seams. Make double topstitch at 0.1 and 0.7 cm along front edge and collar

edge. Tack front facing at shoulder seams.

12. Sew elbow seam, press it apart, serge or finish edges. Sew sleeve front seam, press it apart, serge or finish edges. Sew a gathering stitch along sleeve cap for ease. Gather the fabric slightly between marks.

13. Sew sleeves into armholes matching marks and easing along sleeve cap. Press seams, serge or finish.

14. Serge or finish garment bottom edge. Press the hem under and make double topstitch at 0.7 and 1.4 cm distance.

15. Make buttonholes on right front according to marks. Sew buttons on left.

16. Fold the belt along the center, right sides together. Sew short ends and long side, leaving an opening for turning. Turn right side out, slipstitch opening closed. Sew a double topstitch at 0.1 cm and 0.5 cm distance along belt perimeter.

TECHNICAL DRAWING:

