

## Sewing Pattern — Coat 4247

Please note: closure on collar meets edge to edge

Recommendations on fabric: natural or mixed lightweight fabrics suitable for coats

You will also need: fusible interfacing; lining; raglan shoulder pads; decorative hang closure

If the pattern has a double line around it, the seam allowances are included.

**Note:** By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam allowance: all seams - 1 cm; on hem of the garment and hem of sleeve - 3 cm

Attention! First of all, please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches. They must match up with corresponding pieces.

### **CUTTING:**

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Darts: The fold of the dart is always pressed toward the center of your garment, or down toward the hem.

#### Fabric:

1. Back – cut 1 on fold
2. Front – cut 2
3. Back sleeve – cut 2
4. Front sleeve – cut 2
5. Collar – cut 2
6. Back neck facing – cut 1
7. Front band facing – cut 2
8. Placket – cut 4
9. Large pocket bag – cut 2
10. Closure loop – cut 1

#### Lining:

1. Back – cut 2



2. Front – cut 2
3. Back sleeve – cut 2
4. Front sleeve – cut 2
5. Small pocket bag – cut 2

Fusible interfacing:

1. front band facing – cut 2
2. Back neck facing – cut 1
3. Upper collar – cut 1
4. Placket – cut 2

\*Apply fusing to hem of the garment and hem of sleeve as well.

\*ATTENTION: front and back of lining are cut according to main fabric patterns excluding the width of front band facing and of back neck facing, correspondingly.

### **INSTRUCTIONS:**

1. Apply fusible interfacing to listed pieces.
2. Sew darts on front and press toward hem.
3. Sewing the pocket: If seam allowances are self-added, cut off corners on small pocket bag exactly along cross markers. Fold plackets pairwise together and sew along inner contour. Trim seam allowances, turn details out and press. Make a slit for the pocket on front. Trim seam allowances along round edge carefully, leaving 2-3 mm to placket connection line. Sew plackets to front, matching notches. Press seams from center of pocket. Trim seam allowances carefully along round edge on small pocket bag, leaving 2-3 mm to connection line. Put small pocket bag on top of plackets right side downwards and sew to plackets: along lower half- circle exactly between cross notches. Turn pocket bag downwards and press. Sew top pocket bag to plackets: along upper half-circle exactly between cross notches. Sew outer edge of pocket bags.
4. Sew back sleeve to back, press seams apart. Sew front sleeve to front, press seams apart. Sew top seam of sleeves. Press seams apart. Sew lower sleeve seam and side seam with one stitch. Press seams apart.
5. Sew shoulder seams of back neck facings and front band facing. Press seams apart.
6. Sew upper collar into the neckline, sew lower collar into the neckline of facing. Press seams apart.
7. Pin facing to front, right sides together, and sew center front edge and collar. Trim corners, turn onto right side and straighten. Press collar and center front. Put a fixing stitch along collar and neckline connecting seam. Sew shoulder pads.
8. Sew lining the same way as main fabric, leaving a slit in lower seam of right sleeve. Sew lining to inner edges of facing. Sew lower edge of facing, right side together, along hemline, trim corners. Mark hem of the garment and press onto wrong side. Sew hem of the garment and hem of sleeve with lining. Turn garment out through the slit in sleeve and sew the slit closed.
9. Fold closure loop in half lengthwise, right sides together, and sew along the long side. Turn closure loop onto right side, press and cut into 2 parts. Run one end of the closure loop through the closure and topstitch. Adjust length of closure loops according to closure location. Topstitch second end of the closure loop onto collar according to technical drawing.

**TECHNICAL DRAWING:**

