

## Sewing Pattern — Mantle With Large Collar 5724

Recommendations on fabric: soft wool.

You will also need: lining, fusing, 1 hook.

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: 1 cm for all seams, 3 cm for hem allowance.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



### **CUTTING:**

#### Fabric:

1. Back part – 1 piece
2. Front part – 2 pieces
3. Outer collar – 1 piece
4. Inner collar – 2 pieces
5. Front band – 2 pieces
6. Back neckline facing – 1 piece

#### Lining:

1. Back part – 1 piece
2. Front part – 2 pieces

**NB:** when cutting lining front/back pieces, do not take into account front bands/back neckline facing widths correspondingly.

Fusing: front bands, back neckline facing.

## **INSTRUCTIONS:**

1. Apply the fusing to wrong side of front bands and back neckline facing.
  2. Stitch middle edge of inner collar. Press seam allowances apart. Tack pleats into outer collar. Lay collars right sides together and overstretch along collar falls. Turn the collar right side out, press it.
  3. Stitch shoulder edge.
  4. Stitch shoulder edges of front bands and facing. Press seam allowances apart. Lay front bands on front parts right sides together, insert the collar between them and overstretch along front edging and the neckline.  
Stitch shoulder edges of lining pieces excluding a hole to turn the garment right side out. Stitch the lining to front bands and to neckline facings. Overstretch lower corner. Slash rounded allowances, cut corners.
- Mark garment hem and press it into wrong side. Overstretch the hem with the lining.  
Turn the mantle right side out, then press it.  
Sew technological hole.
5. Make decorative stitch along front edging and garment hem at 1 cm from the edge.
  6. Sew a hood under right front part, sew a ring to the left one.

## **TECHNICAL DRAWING:**

