

Sewing Pattern — Cape 5720

Recommendations on fabric: tweed (or natural/mixed fabric suitable for coats)

You will also need: lining, fusible interfacing, 5 buttons

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam allowance: 1.5 cm for all seams

Attention! First of all, please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches. They must match up with corresponding pieces.



CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Main fabric:

1. Back – cut 1
2. Front – cut 2
3. Sleeve –cut 2
4. Stand-up Collar – cut 2
5. Front band facing – cut 2
6. Back neck facing – cut 1

Lining:

1. Back – cut 1
2. Front – cut 2
3. Sleeve – cut 2

*Note: Cut lining front/back pieces same as main fabric excluding width of front band facing and back neck facing

Fusible interfacing:

1. Stand-up collar – cut 1
2. Front band facing – cut 2
3. Back neck facing –cut 1

INSTRUCTIONS:

1. Apply fusible interfacing to wrong side of front band facings, back neck facing and outer stand-up collar.
2. Pin collar right sides together, and sew outer edges. Trim corners, turn right side out, and press.
3. Sew shoulder seams. Press seam allowances apart.
4. Sew sleeves to front/back. Press seam allowances toward sleeves.
5. Sew shoulder seams of back neck facing and front band facings. Press seam allowances apart. Sew lining pieces together same as main fabric leaving an opening in sleeve right front seam for turning. Sew the lining to inner edges of facing. With lining and fabric right sides together, insert ready collar between them, then sew along front edge, neckline, and hem. Clip into curves, trim corners, turn right side out, then press.
Sew opening closed. Make a decorative stitch along front edge and collar.
6. For belt openings: cut four fabric rectangles - 4x9 cm. Apply fusible interfacing to the wrong side, serge along perimeter. Lay them on slit mark, right sides together, then sew along mark (the cape is already with the lining, stitch it through). Slit the fabric between stitches and make diagonal snips at 1-1.5 cm from short edges. Turn the facing onto the wrong side through this opening. Make decorative/fixing stitch along edges of opening.
7. Make buttonholes on right front, sew buttons to left one.

TECHNICAL DRAWING:

