

Sewing Pattern — Mantle Trimmed with Inkle 5719

Recommendations on fabric: sheer natural/mixed fabrics.

You will also need: lining, fusing, wide inkle (see approximate length on sleeve pattern), clasp.

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: 1 cm for all seams.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Back part – 2 pieces
2. Front part – 2 pieces
3. Sleeve – 2 pieces
4. Front band – 2 pieces
5. Back neckline facing – 2 pieces

Lining:

1. Back part- 2 pieces
2. Front part – 2 pieces
3. Sleeve – 2 pieces

Fusing:

1. Front band – 2 pieces
2. Back neckline facing – 2 pieces

NB: when cutting lining front/back pieces, do not take into account front bands/back neckline facing widths correspondingly.

INSTRUCTIONS:

1. Apply the fusing to wrong side of front bands and back neckline facing.
2. Stitch back middle edge. Slash rounded allowances and press them apart.
3. Stitch shoulder edges. Slash rounded allowances and press them apart.
4. Stitch sleeves to front/back parts. Press seam allowances toward sleeves.
5. Stitch middle of back neckline facing. Press seam allowances apart. Stitch shoulder edges of front bands and facings. Press seam allowances apart.
Stitch lining pieces together leaving a hole into sleeve right front seam (to turn the garment right side out).
Stitch the lining to front bands and back neckline facing.
Lay front bands with the lining on the garment right sides together and overstretch around along front edging/neckline/hem.
Slash rounded allowances, cut corners, turn the garment right side out, then press.
Sew technological hole.
6. Cut four fabric quadrates of 4x9 cm. Apply the fusing, neaten along perimeter. Lay them on slit marking right sides together, then stitch along marking. Slit the fabric between stitches as for slit pocket. Make diagonal slashes at 1-1.5 cm from short edges. Turn the facing into wrong side trough this hole. Make decorative/fixing stitch along edges of this hole.
7. Topstitch the inkle along lapel edges/front edgings, garment/sleeve hems.
8. Fold the waistband along the center wrong side out, overstretch along thee edges leaving a hole into waistband upper seam. Cut seam allowances in corners, turn the waistband right side out, stitch the hole. Pull the waistband into clasp and fix it. Set eyelets.

Our advice: you can use ready belt as a waistband.

TECHNICAL DRAWING:

