

## Sewing Pattern — Soft Wool Mantle 5717

Recommendations on fabric: soft wool (easy to drape).

You will also need: piping.

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: 0 cm for garment/sleeve hems as well as for hood edge and front edging. 1 cm for other seams.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



### **CUTTING:**

Fabric:

1. Back part – 1 piece
2. Front part – 2 pieces
3. Sleeve – 2 pieces
4. Hood – 2 pieces
5. Waistband – 1 piece
6. Belt loop – 1 piece

### **INSTRUCTIONS:**

1. Stitch hood middle edge. Press the seam. Press the piping along the center. Trim seam allowances with the piping.
2. Stitch shoulder edges. Neaten seams and press them backward.
3. Stitch the hood into neckline. Press seam toward the hood. Trim seam allowance with the piping.
4. Trim sleeve hems with the piping.
5. Stitch sleeves into open armholes.
6. Stitch sleeve edge/side edge with one seam. Press the seam apart.
7. Trim garment hem with the piping. Trim front edging and hood edge. Press front edging as marked, then stitch.
8. Fold belt loop wrong side out, then stitch. Turn the detail right side out, then press. Cut the loop into 4 pieces. Sew belt loops to marked lines on front/back parts.
9. Fold the waistband along the center wrong side out, overstitch it along three edges leaving 7-10 cm

segment in the middle of long edge. Turn the waistband tight side out and press it. Make decorative stitching at 0.5 cm from the contour stitching the hole.

**TECHNICAL DRAWING:**

