

Sewing Pattern — Mantle 5714

Recommendations on fabric: faux fur (short hair)

You will also need: lining, fusible interfacing, 3 buttons

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam allowance: 3 cm for garment hem; 1.5 cm for front/back shaped edges, 1 cm for other seams

Attention! First of all, please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches. They must match up with corresponding pieces.



CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Darts: The fold of the dart is always pressed toward the center of your garment, or down toward the hem.

Fabric:

1. Front – cut 2
2. Back – cut 1
3. Back sleeve – cut 2
4. Front sleeve – cut 2
5. Collar – cut 2
6. Front band facing – cut 2
7. Back neck facing – cut 1

Lining:

1. Front – cut 2
2. Back – cut 1
3. Back sleeve – cut 2
4. Front sleeve – cut 2

*Note: Exclude front band facing and neck facing widths when cutting lining front/back.

Fusible interfacing:

1. Back neck facing – cut 1
2. Front band facing – cut 2
3. Collar – cut 1

*Note: we recommend that you test sew with faux-fur scraps prior to sewing garment.

INSTRUCTIONS:

1. Apply the fusible interfacing to wrong side of collar, front band facings and back neck facing.
2. Sew front upper dart. Slash dart depth and press it apart.
3. Sew front/back shaped edges, press seams apart.
4. Pin front band facing on front, right sides together, then sew along center front; sewing from front side up to the notch for collar stitching end. Sew front band facing hems to front along marked hemline. Trim corners. Turn facing under and press.
5. Sew shoulder seams together, press seams apart.
6. Pin collars right sides together. Sew outer edges of collar together stopping at joining stitch line. Clip into curves and trim corners. Turn the collar right side out, then press.
7. Sew shoulder seams of back neck facing and front band facings. Press seams apart.
8. Sew lining together.
9. Pin the collar between the garment and the lining. Sew outer collar into garment neckline, sew inner one into facing neckline. Press seam allowances apart. Turn facing onto wrong side, and stitch allowances of seams joining collars close to seams.
10. Press garment hem under. Sew the hem with blind stitches.
11. Pin the lining on the garment, right sides together, then stitch to front band facing inner edges/back neck facing at 10 cm from the hem line. Sew the lining to back/front slits. Adjust lining hem to garment hem. Fold lining hem twice and topstitch. Sew the rest of the lining to front band facing. Sew slit allowances to main pieces by hand or fix them with glue net.
12. Make buttonholes on right front, sew buttons on left.

TECHNICAL DRAWING:

