

Sewing Pattern — Zip-up Cape 5713

Recommended fabric: whipcord (a cotton, woolen, or worsted fabric with a steep, diagonally ribbed surface).

You will also need: separating zip with upper and lower sliders, fusible interfacing

If the pattern has a double line around it, the seam allowances are included.

Seam allowance: 1.5 cm for the hem; 1 cm for other seams.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Darts: The fold of the dart is always pressed toward the center of your garment, or down toward the hem.

Main fabric:

1. Front – cut 2
2. Back – cut 2
3. Hood – cut 2
4. Hood center – cut 1
5. Off-set welt – cut 2
6. Large sacking – cut 2
7. Small sacking – cut 2
8. Front band – cut 2

Lining:

* We recommend using the same fabric for lining.

1. Hood – cut 2
2. Hood center – cut 1

Fusing: Off-set welt – cut 2, Front band – cut 2

INSTRUCTIONS:

1. Apply interfacing to wrong sides of front bands and off-set welts.
2. Apply interfacing to wrong side of pocket place. Press the welt along the center right side out. Mark a line on welt to define ready off-set welt's width. Sew small sacking to welt's wrong side. Lay the welt with sacking on front, right sides together, matching pocket marking and line on the welt. Sew the off- set welt. Sew large sacking to pocket marking's upper line. Cut pocket entrance between markings, snipping diagonally toward end of stitching. Turn pocket onto wrong side, through the slit. Press seam allowances. Stitch sacking edges fixing pocket corners. Cut 2 fabric strips of 2 x15 cm for sacking holder. Sew one end to sacking edge. Lay front on smooth surface, make holder's other end equal to front edge. Sew holder's end to front edge. Cut extra fabric off holder. *There are many ways to construct the single welt pocket, here is a great video that may assist you: [Single Welt Pocket](#)
3. Sew center back seam. Serge and press seam toward left.
4. Sew shoulder seams together. Serge and press seam toward back.
5. Sew hood to hood center on fabric and lining. Sew the hood into the neckline.
6. Lay half of zipper on center front, right sides together (with its teeth against front edging). Sew the zipper in.
7. Serge the front band's outer edge. Sew front band to hood lining. Press the seam toward the hood. Lay front band on front, right sides together, then sew front edge as well as hood. Press the seam. Fix together seam allowances on center of hood (fabric and lining). Fold hood lining's raw edge under, and topstitch into neckline seam.
8. Serge the lower edge of garment, turn onto wrong side, and topstitch.

TECHNICAL DRAWING:



