

Sewing Pattern — Long-Hair Fur Jacket 5712

See details for work with faux fur at *How to use the CD*.

Recommendations on fabric: faux fur.

You will also need: lining, 3 coat hooks.

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: 1.5 cm for all seams, 4 cm for garment/sleeve hems.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fur:

1. Back yoke – 1 piece
2. Lower back part – 1 piece
3. Front yoke – 2 pieces
4. Lower front part – 2 pieces
5. Sleeve – 2 pieces
6. Inner collar – 1 piece
7. Outer collar – 1 piece
8. Valance – 2 pieces

Lining:

1. Back yoke – 1 piece
2. Lower back part – 1 piece
3. Front yoke – 2 pieces
4. Lower front part – 2 pieces
5. Sleeve – 2 pieces
6. Upper sacking – 2 pieces
7. Lower sacking – 2 pieces

NB: when cutting lining front yoke/lower front, do not take into account front bands width.

INSTRUCTIONS:

1. Stitch the valance to lower sacking. Lay the sacking with the valance on back part's right side, lay lower sacking's right side on front part, then stitch. Fold the seam out and topstitch on the sacking.
2. Stitch back yoke to lower back part.
3. Stitch front yoke to lower front parts.
4. Stitch shoulder edges.
5. Lay collars right sides together and overstretch them along corners/collar fall. Turn the collar right side out. Tack the collar into the neckline.
6. Stitch sleeves into armholes.
7. Stitch sleeve edge/side edge with sackings with one seam.
8. Do the same to stitch lining pieces together: stitch the yoke to back part, stitch front yoke to front part. Stitch side/sleeve seams leaving a hole in sleeve front right seam (to turn the garment right side out). Stitch shoulder edges at 5 cm distance from armhole edges. Stitch front part lining to front band edges. Stitch shoulder seams to the end. Stitch sleeves into armholes.
9. Lay the lining and front bands on the garment right sides together, then overstretch the neckline. Stitch front bands' lower edges to front parts as marked on the hem. Cut seams in front edgings' lower corners.
10. Stitch the lining to garment/sleeve hems. Turn the jacket right side out through sleeve hole. Stitch hole edges together.
11. Sew hooks under right front edging. Lay right front part on left front part coinciding middle lines, then mark loop places. Sew loops to left front edging.

TECHNICAL DRAWING:

