

## Sewing Pattern — Blouse 4245

Recommendations on fabric: natural or mixed knit fabric of medium stretchiness

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: hem, hem of sleeve – 1.5 cm, all other seams - 0.8 cm

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



### **CUTTING:**

#### Main fabric:

1. Front part – 1 detail
2. Back part – 1 detail
3. Collar – 1 detail
4. Sleeve – 2 details

#### Advice:

Knitted fabric details are sewn together with special elastic or narrow zig-zag stitch. When serging cut seam allowances to 0.6 – 0.8 cm. Seam allowance on turnup is stitched with twin needles to save stretchiness. Details also can be sewn together via 3 or 4 – threaded serger.

**INSTRUCTIONS:**

1. Sew shoulder and side edges. Serge and press seam allowances towards back part.
2. Sew edge of sleeve. Serge and press seam allowance onto back part. Sew sleeve into armhole, leveling notches. Serge seam allowance.
3. Stitch loosely along front part lower neckline edge between round markers and gather ruffles.
4. Fold collar in half lengthwise wrong sides together and fix on all edges. Crossover ends of collar (right end is on top), align edges and fix along edges. Sew collar into the neckline, slashing in corners. Serge seam allowances.
5. Serge hem of garment and lower edge of sleeve. Turn onto wrong side, press and topstitch.

**TECHNICAL DRAWING:**