

## Sewing Pattern — Fur jacket 5709

Recommendations on fabric: faux fur.

You will also need: lining; faux leather

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Seam allowance: 0.5 cm for all seams, 4 cm for the hem/sleeve hems

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



### **CUTTING:**

#### Fur:

1. Back part – 1 piece
2. Front part – 2 pieces
3. Sleeve – 2 pieces
4. Belt – 1 piece
5. Back neckline facing – 1 piece
6. Belt loop – 1 piece
7. Valance – 2 pieces
8. Hood – 2 pieces

#### Lining:

1. Back part – 1 piece
2. Front part – 2 pieces
3. Sleeve – 2 pieces
4. Upper sacking – 2 pieces
5. Lower sacking – 2 pieces

**NB:** when cutting lining front/back pieces, do not take into account front bands/back neckline facing widths correspondingly.

### **INSTRUCTIONS:**

1. Stitch the valance to lower sacking. Lay the sacking with the valance on back part's right side according to notches, lay upper sacking's right side on front part, then stitch. Fold the seam out and topstitch it on the sacking.

2. Stitch shoulder seams.
3. Stitch hood middle edges together. Slash seam allowance at neck base. Stitch the hood into the neckline.
4. Stitch sleeves into armholes.
5. Stitch sleeve edges/side edges with sackings with one seam.
6. Cut belt loops of faux leather. Roll loops in 3 layers and topstitch long edges at 0.2 cm from edges. Topstitch belt loops on side seams according to marks. **Our advice:** you can topstitch additional belt loop on right front edging's right side at side loops level to make garment more comfortable.
7. Stitch back neckline facing to front bands. Stitch inner hood's middle edges. Slash seam allowance at neck base. Stitch the hood into facing neckline. Press one-piece front bands into wrong side. Fix middle seam allowances of both hoods together.
8. Cut 2 ties of the lining: 40 cm length and 4 cm width. Press ties along the center right side out. Lay them flat and press long edges toward the center. Then fold a tie along the center again and topstitch it at 0.1 cm from edges. Sew ties to left front band and to right side lining seam at waistline level.
9. Stitch lining pieces excluding a hole into sleeve left seam (to turn the garment right side out). Lay the lining on the jacket right side together and stitch to front bands' inner edges/back neckline facing. Overstitch front edgings' lower corner strictly along marked hem. Cut seams in front edgings' lower corners. Fold lining sleeves under and stitch them to jacket's sleeve hems.
10. Stitch the lining to jacket hem. Turn the jacket right side out through sleeve hole, stitch hole edges together.
11. Lay the belt wrong side out and overstitch it along outer contour excluding a hole in the middle of upper seam. Turn the belt right side out and stitch hole edges together.

### TECHNICAL DRAWING:

