

Sewing Pattern — Jacket 5708

Recommendations on fabric: faux sheepskin, faux fur with long hair (collar)

You will also need: 2 decorative fastenings

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam allowance: 0 cm for all open edges (front edging, the hem, cuff edges, collar fall); Use lap seam for front/back relieves and sleeve front seams (see detailed instructions); 1.5 cm for other seams

Attention! First of all, please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches. They must match up with corresponding pieces.

CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Darts: The fold of the dart is always pressed toward the center of your garment, or down toward the hem.

Faux sheepskin:

1. Side front – cut 2
2. Side back – cut 2
3. Center back – cut 2
4. Front yoke – cut 2
5. Center front– cut 2
6. Upper sleeve – cut 2
7. Lower sleeve – cut 2
8. Cuff – cut 2

Fur:

1. Collar – cut 1



INSTRUCTIONS:

1. Sew the yoke to center front. Lay seam allowances apart and topstitch them.
2. Sew side front to center front with lap seam.
3. Sew side backs to center backs with lap seams.
4. Sew center back seam. Lay seam allowances apart and topstitch them.
5. Sew shoulder/side seams. Lay seam allowances apart and topstitch them.
6. Sew sleeve front edge with lap seam. Lay a cuff on a sleeve, furry side together, and sew together with closed seam, trim cuff seam allowance and topstitch sleeve allowance. Sew sleeve elbow seams. Make notches in elbow seam allowances at cuff joining seam, then topstitch elbow seam allowances on the cuff with closed seam.
7. Sew sleeves into armholes according to notches. Make notches in seam allowances, lay seam allowance apart, then topstitch sleeve allowance on the sleeve, topstitch armhole allowance on front and back.
8. Sew the collar to the garment.
9. Make a fixing stitch at 0.1-0.2 cm from edges along front edges, the hem, and cuff edges. Sew fastenings. Make decorative stitch at 2 cm from edges along front edges and the hem.

TECHNICAL DRAWING: