

Sewing Pattern — Jacket 5705

Recommendations on fabric: faux leather

You will also need: lining; fusible interfacing; 1 separating zipper; a snap

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam allowance: 1 cm for all seams, 4 cm for sleeve hems

Attention! First of all, please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches. They must match up with corresponding pieces.

CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Leather:

1. Stand-up collar – cut 1
2. Back – cut 2
3. Back yoke_1 – cut 2
4. Back yoke_2 – cut 2
5. Back yoke_3 – cut 2
6. Front – cut 2
7. Front yoke_1 – cut 2
8. Front yoke_2 – cut 2
9. Front yoke_3 – cut 2
10. Back waistband – cut 2
11. Front waistband – cut 4
12. Upper sleeve – cut 2
13. Lower sleeve – cut 2
14. Front band facing – cut 2
15. Back neck facing – cut 1

Lining:

1. Back – cut 2
2. Front – cut 2
3. Upper sleeve – cut 2
4. Lower sleeve – cut 2



Fusible interfacing: front band facing, front/back waistband, stand-up collar

Note: please try sewing together scraps of leather before you sew garment.

INSTRUCTIONS:

1. Apply interfacing to wrong side of front band facing, front/back waistband and stand-up collar.
2. Sew front upper darts. Slash depths, fold them downward and topstitch.
3. Sew front yoke_1 to front yoke_2, topstitch seam allowances on yoke_1. Sew front yoke_3 to front yoke_2, topstitch seam allowances on yoke_2. Sew the whole yoke to front, topstitch seam allowances on the yoke.
4. Sew back yoke_1 to back yoke_2, topstitch seam allowances on yoke_1. Sew back yoke_3 to back yoke_2, topstitch seam allowances on yoke_2. Sew the whole yoke to back, topstitch seam allowances on the yoke. Sew center back seam, press seam allowances toward the left, and topstitch.
5. Mark zipper closures on patch pockets. Cut slits according to marks, make diagonal slits at 1-1.5 cm from closure ends. Fold allowances onto wrong side, lay the zipper under slit allowances with its teeth visible, then topstitch along the perimeter at 0.2 cm from edges. Fold flap pocket's edges onto wrong side and topstitch on front/left sleeve according to marks.
6. Stitch shoulder/side seams. Press seams apart and using appropriate adhesive, glue them down.
7. Sew front waistbands to back waistbands. Press seams apart and using appropriate adhesive, glue them down. Sew outer waistband to jacket hem. Fold seam allowances downwards, then topstitch.
8. Pin fronts right sides together and adjust edges, measuring center front length. Sew the zipper to center front edges.
9. Fold the stand-up collar right sides together along the center and sew outer edges up to the first mark. Trim corners and turn right side out. Make decorative stitch along the edge.
10. Baste the stand-up collar into jacket neckline.
11. Sew elbow edge. Fold the seam upward, then topstitch. Press sleeve hem onto wrong side. Sew sleeve front edge folding hem allowance out. Sew sleeves into armholes according to notches. Fold seam allowances toward the garment, then topstitch.
12. Sew shoulder seams of front band facings/back neck facing and press seams apart. Sew lining together same as main fabric, leaving an opening in a sleeve right seam for turning. Sew the lining to inner edges of facing. Sew lower waistband to the lining.
13. Pin ready lining to the jacket, right sides together, and sew the hem/front edges with one seam as well as sewing the stand-up collar in. Sew sleeve lining to sleeve hems. Turn the jacket right side out through sleeve opening. Sew opening closed. Make decorative stitch along the zipper and hem. Divide lower waistband into three sections and topstitch them as shown.
14. Set a snap into the stand-up collar.

TECHNICAL DRAWING:

