

Sewing Pattern — Jacket 5704

Recommendations on fabric: faux leather.

You will also need: lining; fusing; 1 separable zipper; fur (collar and cuffs); 8 snaps; 4 decorative rings

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Seam allowance: 1 cm for all seams, 4 cm for the hem.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Faux leather:

1. Back part – 2 pieces
2. Front yoke – 2 pieces
3. Lower front part – 2 pieces
4. Back sleeve – 2 pieces
5. Front sleeve – 2 pieces
6. Cuff – 2 pieces
7. Front band – 2 pieces
8. Inner collar – 1 piece
9. Back neckline facing – 1 piece
10. Left belt_1 – 2 pieces
11. Left belt_2 – 2 pieces
12. Left belt_3 – 2 pieces
13. Left belt_4 – 2 pieces
14. Right belt_1 – 2 pieces
15. Right belt_2 – 2 pieces
16. Right belt_3 – 2 pieces
17. Right belt_4 – 2 pieces

Fur:

1. Outer collar – 1 piece
2. Cuff – 2 pieces

Lining:

1. Back part – 2 pieces
2. Front yoke – 2 pieces
3. Lower front part - 2 pieces
4. Back sleeve – 2 pieces
5. Front sleeve – 2 pieces

NB: when cutting lining back part, yoke and lower front part, do not take into account front bands/back neckline facing widths correspondingly.

Fusing: front band, back neckline facing.

NB: please try faux-leather details of unneeded material before you double them of the leather.

INSTRUCTIONS:

1. Apply the fusing to wrong side of front band and back neckline facing.
2. Stitch front yoke to lower front part. Fold seam allowance toward the yoke, then paste.
3. Lay front parts right sides together and adjust edges coinciding yokes, then measure front edgings' lengths. Stitch the zipper to front edging.
4. Lay belts right sides together and overstitch along three edges. Cut seams, turn belts right side out and made topstitching along perimeters. Set upper snaps into belt ends.
Lay belts on front part as marked, adjust lengths and mark lower snaps place. Set lower snaps.
Topstitch belts on front parts.
5. Stitch middle back seam. Fold allowances leftward, then topstitch. Stitch back sleeves to back part. Stitch front sleeves to front parts.
6. Stitch sleeve upper edges. Fold seam allowances apart and topstitch them. Lay cuffs on sleeves right sides together, then stitch. Fold seams toward cuffs, then paste. Stitch sleeve lower edges/side edges with one seam.
7. Lay collar s right sides together and overstitch along ends/collar falls. Turn the collar right side out. Tack the collar into the neckline.
8. Stitch fur cuff as a ring, lay it on inner cuff right sides together, then overstitch lower edge. Turn the cuff right side out.
9. Stitch front band/facing shoulder edges and press them apart. Lay front band on front part right sides together, adjust edges and overstitch lower corner/front edging with one seam, as well as stitch the collar in. Cut front edging upper/lower corners' seams. Turn front edgings right side out. Make decorative stitch along the zipper.
10. Stitch lining pieces together and stitch sleeves in leaving a hole in sleeve right front seam. Press lining allowances into wrong side. Stitch the lining to front band inner edges and to the facing.
11. Press jacket hem into wrong side. Overstitch the hem/sleeve hems with the lining. Turn the jacket right side out through the sleeve hole. Stitch hole's edges together.

12. Pull belts into rings and fasten snaps.

TECHNICAL DRAWING:

