

Sewing Pattern — Jacket with belt 5703

Recommendations on fabric: faux leather.

You will also need: lining, 4 buttons, a clasp

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Seam allowance: 4.5 cm for hem/sleeve hems, 4 cm for pocket upper edge, 1 cm for other seams

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Faux leather:

1. Back part – 1 piece
2. Front part – 2 pieces
3. Sleeve – 2 pieces
4. Cuff – 2 pieces
5. Belt – 1 piece
6. Belt loop – 1 piece
7. Back neckline facing – 1 piece
8. Front band – 2 pieces
9. Outer collar – 1 piece
10. Inner collar – 1 piece
11. Pocket – 1 piece
12. Flap – 1 piece

Lining:

1. Back part – 1 piece
2. Front part – 2 pieces
3. Sleeve – 2 pieces
4. Pocket – 1 piece
5. Flap – 1 piece

NB: when cutting lining front/back pieces, do not take into account front bands/back neckline facing widths correspondingly. When cutting lining sleeves, do not take into account cuff width.

NB: please try faux-leather details of unneeded material before you double them of the leather

INSTRUCTIONS:

1. Lay flaps right sides together, then overstitch along 3 edges. Cut flap corners' allowances and turn the detail right side out. Press seams. Neaten flap's free edge. Make a buttonhole as marked.
2. Stitch pocket lining to one-piece facing of pocket upper edge leaving a 5-cm segment at seam middle (to turn the pocket right side out). Overstitch pocket side/lower edges with the lining. Turn the pocket right side out, then press. Make decorative stitch at 3 cm from pocket upper edge stitching the hole. Mark upper pocket place on front part, then stitch the pocket. Stitch the flap on front part, fold it under, then topstitch.
3. Lay outer collar on inner one, then overstitch. Cut seams at corners, turn the collar right side out, then press.
4. Lay front band on front part right sides together, then overstitch along front edging. Overstitching goes at front part up to the notch defining collar stitching-in end. Cut front edging upper corners' seams. Turn front edgings right side out.
5. Stitch shoulder seams, press them apart.
6. Stitch shoulder edges of back neckline facing and front bands. Press seams apart. Insert the collar between the jacket and front bands. Stitch inner collar into jacket neckline, stitch outer collar into facing/front bands neckline. Press inner/outer collar joining seams' allowances apart. Fold front bands into wrong side. Coincide seams. Make topstitching on outer collar strictly along the seam joining the collar to the neckline.
7. Stitch armholes into open armholes.
8. Stitch sleeve edge/side edge with one seam., press allowances apart.
9. Fold belt loop in 3 layers then stitch. Cut the loops into 2 pieces. Sew belt loops to side seams as marked.
10. Stitch a cuff as a ring, press the seam apart. Stitch the cuff to sleeve hem. Turn details right side out, then press.
11. Stitch lining details excluding a segment into sleeve left seam (to turn the garment right side out). Lay the lining on the garment right sides together and stitch to front bands' inner edges and to back neckline facing. Overstitch front edging's lower corner. Cut front edging lower corners' seam. Stitch sleeve lining to the cuff.
12. Stitch the lining to jacket hem. Turn the jacket right side out through sleeve hole, stitch hole's edges together.

13. Fold the belt along the center wrong side out, overstitch along edges leaving 7-10 cm hole in the middle of long edge. Turn the detail right side out, then press. Make decorative stitching along contour at 0.5 cm distance stitching the hole. Set the clasp.

14. Make buttonholes into right front edging, sew buttons on the left on. NB: make buttonholes into both front lapels.

TECHNICAL DRAWING:

