

## Sewing Pattern — Jacket 5702

Recommendations on fabric: faux leather, leather

You will also need: lining; fusible interfacing; 1 separating zipper

If the pattern has a double line around it, the seam allowances are included.

**Note:** By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam allowance: 1 cm for all seams, 4 cm for the hem/sleeve hems.

Attention! First of all, please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches, they must match up with corresponding pieces.



### **CUTTING:**

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

**Recommendation:** Use faux-leather and make a muslin before cutting into your more expensive fashion leather.

### Leather:

1. Outer stand-up collar – cut 1
2. Inner stand-up collar – cut 1
3. Center back – cut 2
4. Side back – cut 2
5. Side front –cut 2
6. Center front – cut 2
7. Front facing/band – cut 2
8. Upper sleeve – cut 2
9. Lower sleeve – cut 2
10. Back neck facing – cut 1

### Lining:

1. Center back – cut 2
2. Side back – cut 2

3. Center front – cut 2
4. Side front – cut 2
5. Upper sleeve – cut 2
6. Lower sleeve – cut 2

Note: cut lining front/back pieces, using main pattern pieces, but exclude front facing/bands and back neck facing widths correspondingly.

Interfacing: front facing bands, stand-up collars, back neck facing.

### **INSTRUCTIONS:**

1. Apply the interfacing to wrong side of front facing/bands, stand-up collars and back neck facing.
2. Sew front waist darts and back shoulder darts. Trim dart depths.
3. Sew side fronts to fronts.
4. Sew side backs to backs. Sew center back seam.
5. Sew shoulder/side edges. Sew outer stand-up collar to neckline. Sew front neck dart and stand-up collar with one seam.
6. Lay fronts, right sides together, and adjust edges, making sure length is even. Lay the zipper on front, right sides together (zipper teeth align with seam marked line and zipper tape is on allowances), baste.
7. Sew sleeve elbow and sleeve front seams. Press sleeve hem onto wrong side. Sew sleeves into armholes, matching notches.
8. Sew front facing/bands to back neck facing, press seam apart. Sew inner stand-up collar to the neckline. Sew lining pieces together, then sew sleeves in, leaving an opening in the right front seam for turning garment right side out. Press lining seam allowances. Sew the lining to the facing inner edges.
9. Pin the front facing/band to lining on front, right sides together, then sew lower corner/front edge/stand-up collar upper edge (catching the zipper) with one seam. Trim front upper and lower corner seams. Turn front right side out. Topstitch along front edge and stand-up collar upper edge at 0.5 cm from edge.
10. Press jacket hem onto wrong side. Sew the hem and sleeve hems to the lining. Turn the jacket right side out through sleeve opening. Slipstitch the opening closed.

### **TECHNICAL DRAWING:**

