

## Sewing Pattern — Large-collar jacket 5701

Recommendations on fabric: faux fur, faux leather.

You will also need: lining, fusing, 1 separable zipper

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Seam allowance: 1.5 cm for all seams.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



### **CUTTING:**

#### Faux fur:

1. Back sleeve – 2 pieces
2. Front sleeve – 2 pieces
3. Back part – 1 piece
4. Front part – 2 pieces
5. Hood – 2 pieces

#### Faux leather:

1. Back placket – 1 piece
2. Lower front placket – 2 pieces
3. Front placket – 4 pieces
4. Hood placket – 1 piece
5. Cuff – 2 pieces
6. Valance – 2 pieces

#### Lining:

1. Back sleeve – 2 pieces
2. Front sleeve – 2 pieces
3. Back part – 1 piece
4. Front part – 2 pieces
5. Hood – 2 pieces
6. Upper sacking – 2 pieces
7. Lower sacking – 2 pieces

Fusing:

1. Back placket – 1 piece
2. Lower front placket – 2 pieces
3. Front placket – 4 pieces
4. Hood placket – 1 piece
5. Cuff – 2 pieces

**NB:** please try faux-leather details of unneeded material before you double them of the leather.

**INSTRUCTIONS:**

1. Apply the fusing to wrong side of faux-leather details.
2. Stitch upper front darts.
3. Stitch the valance to lower sacking. Lay the sacking to valance on back part's right side according to notches; lay upper sacking's right side on front part, then stitch. Fold the seam out and topstitch it on the sacking.
4. Stitch front sleeve to front part. Stitch back sleeve to back part.
5. Stitch shoulder edges together with sleeves' upper edges.
6. Press a cuff along the center right side out. Stitch cuff's upper edge to sleeve hem.
7. Stitch sleeve lower edge and side edge together with sackings.
8. Stitch lower front plackets to lower back placket. Press lower plackets along the center right side out. Stitch placket's upper edge to jacket's hem.
9. Stitch the zipper to front outer plackets' edges. Stitch front plackets to front edges up to the hem allowance.
10. Stitch hood middle edges. Press hood placket along the center right side out. Stitch placket's upper edge to hood outer edge. Fold the placket along the center wrong side out, then overstretch lower corners; do not catch placket inner edge's allowance. Cut corner allowances, turn the placket right side out.
11. Stitch the hood into garment neckline.
12. Stitch lining pieces in the same way as fur ones leaving a hole into left sleeve lower seam (to turn the garment right side out). Stitch the lining to lower placket's edge right sides together. Stitch front inner placket to lining edges to the hem allowance.
13. Lay the lining on the garment right sides together and overstretch front placket's lower corner/front edge/hood inner edge. Overstretch sleeve hems with the lining. Turn the jacket right side out though the hood in the sleeve seam. Fix the lining to the garment along hood middle seam/hood placket/hood joining seam/cuffs/lower placket. Stitch sleeve hole's edges together.
14. Make fixing topstitching along the zipper.

**TECHNICAL DRAWING:**

