

Sewing Pattern — Dress 4244

Recommendations on fabric: natural or mixed knit fabric of medium stretchiness; single-colored companion fabric

You will also need: elastic tape of 1.5 cm wide. (the approximate length is mentioned on the front part p-attern)

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: along neckline – 2 cm, hem — 1.5 cm, all other seams – 1 cm.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Main fabric:

1. Upper back part - 1 folded detail
2. Upper front part - 1 folded detail

Companion fabric:

1. Lower front part - 1 folded detail
2. Lower back part — 2 details

Advice:

Knitted fabric details are sewn together with special elastic or narrow zig-zag stitch. When serging cut seam allowances to 0.6 – 0.8 cm. Seam allowance on turnup is stitched with twin needles to save stretchiness. Details also can be sewn together via 3 or 4 – threaded serger.

INSTRUCTIONS:

1. Sew center edges on lower parts of the back.
2. Stitch lower parts to upper parts. Serge and press seam allowances downwards.
3. Sew shoulder seams. Serge and press towards back part. Serge side edge and edge of sleeve in one step: along side edge of front part, along the front part sleeve edge, along the back part sleeve edge and along side edges of back part. Sew side seams from hem up to marker. Turn seam allowances of sleeve hem inside and topstitch.
4. Serge seam allowance, turn inside and topstitch, leaving a slit. Run the elastic tape through the self-belt and fix ends.
5. Serge hem of the garment, press onto wrong side and topstitch.

TECHNICAL DRAWING: