

Sewing Pattern — Jacket 5699

Recommendations on fabric: faux fur, faux leather

You will also need: lining; fusing; 1 separable zipper, 4 folding clasps, 4 eyelets for the clasp, 1 buckle for the belt.

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: 1 cm for all seams

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Faux fur:

1. Back part of sleeve – 2 details
2. Front part of sleeve – 2 details
3. Back part - 1 detail
4. Front part - 2 details
5. Collar - 1 detail

Faux leather:

1. Back part placket – 2 details
2. Lower placket of front part – 4 details
3. Right placket of front band - 1 details
4. Right inner placket of front band - 1 details
5. Left placket of front band - 2 details
6. Collar - 1 detail
7. Cuff - 2 details
8. Belt – 1 detail
9. Half-belt – 16 details
10. Belt loop – 1 detail

Lining:

1. Back part of sleeve – 2 details
2. Front part of sleeve – 2 details
3. Back part - 1 detail
4. Front part - 2 details

Fusing:

1. Placket of back part – 1 detail
2. Lower placket of front part – 2 details
3. Right placket of front band - 1 detail
4. Left placket of front band - 1 detail
5. Cuff - 2 details

ATTENTION: before applying fusing to details of faux leather, test on a waste piece

INSTRUCTIONS:

1. Apply fusing to details of faux leather.
2. Fold half-belt details together right sides touching and overstretch on three sides. Cut seam allowances off close to the seam. Turn half-belts out, press and stitch along seam line at 0.1 cm.
3. Press right placket on fold line. Fold right placket details (outer and inner plackets) right sides together, insert zipper between them so that zipper blades are turned from the edge. Sew plackets together, connecting right edge of zipper at the same time. Turn inner placket aside, leveling longitudinal edges and shaping by that patch placket. Topstitch seam allowances onto inner placket. Fold left placket details together right sides touching, insert left edge of zipper and sew plackets together. Overstretch plackets along upper and lower edges. Turn details right side out and stitch on three sides at 0.1 cm and at 0.7 cm.
4. Run the end of each half-belt through the folding clasp at the length of 3 cm and topstitch. Overstretch half-belts with eyelets the same way. Pin half-belts with clasps to right placket, half-belts with eyelets – to left placket. Zip up, fasten clasps to eyelets and finally level the length of all half-belts. Sew open edges of half-belts to open edges of plackets. Zip down and then sew plackets as 2 details.
5. Sew bust dart on front part details.
6. Stitch front part of sleeve to front part. Stitch back part of sleeve to back part.
7. Sew shoulder seams together with upper edges of sleeve.
8. Sew lower edge of sleeve and side edge with one seam.
9. Press cuff in half lengthwise wrong sides together. Unfold cuff, fold it right sides together and sew it into ring. Turn the cuff out, press seam apart. Stitch cuff to lower edge of sleeve.
10. Fold the belt loop in 3 layers and sew. Cut the belt loop in 2 details .
11. Stitch lower plackets of front parts to lower placket of back part. Press seams apart. Sew lower edge of belt loops to side seams of outer plackets according to markers. Tack upper end belt-loops to upper edge of plackets.
12. Stitch loosely along lower edge of the jacket and gather a slight ruffle. Stitch outer parts of plackets to lower edge of the jacket.
13. Sew lining details the same way as main fabric details, leaving a slit in lower seam of left sleeve. Stitch lining to inner details of lower placket.
14. Sew upper collar into the jacket neckline. Sew lower collar into the lining neckline. Press seams apart.

15. Fold lining and jacket right sides together, insert front band plackets between them and overstretch front band edge, collar edge and lower edge. Overstretch hem of sleeve with lining. Turn the jacket right side out through the slit in sleeve. Sew slit in sleeve.

16. Put decorative stitch along lower plackets and back part / front part connecting seam and along hem line.

17. Fold belt in half lengthwise right sides together and overstretch on three sides, leaving a slit of 7-10 cm in the center of the long side of the belt. Turn belt out and press. Put decorative stitch at 0.5 cm along the contour, sewing the slit at the same time. Run the buckle.

TECHNICAL DRAWING:

