

Sewing Pattern — Skirt 5697

Recommendations on fabric: well-diapering natural/mixed fabric.

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: 1 cm for all seams, 2 cm for front/back skirts' upper edge as well as for the hem

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Main fabric:

1. Back skirt – 1 piece
2. Front skirt – 1 piece
3. Loop – 2 pieces
4. Tie - 2 pieces

INSTRUCTIONS:

1. Stitch back darts, press them toward the center.
2. Make pleats into front skirt's right side, then stitch them. Press pleats downward.
3. Fold ties along the center wrong side out and overstitch one long/one short edges. Turn details right side out and press them. Topstitch ties at 0.1 cm from edges.
3. Stitch skirt's side edges inserting ties. Press seams backward and neaten them.
4. Press skirt upper edge's allowance into wrong side, fold it under and topstitch.

5. Press the hem into wrong side, fold it under and topstitch.
6. Neaten loops' edges. Press loop long edges into wrong side and topstitch. Fold short edges into wrong side. Lay loops on front/back skirts as marked and topstitch at 0.1 cm from bending.
7. To make the skirt be fasten on the body, we recommend the following: fold the skirt along side seams, displace side seams 2.0-2.5 cm toward front skirt and fix skirts together with a stitch of approximately 10 cm. At waistline bendings: fix front/back skirts together by means of snaps and buttonholes with buttons.

TECHNICAL DRAWING:

