

Sewing Pattern — Tunic 5692

Recommendations on fabric: sheer natural/mixed fabric

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam allowance: 1 cm for all seams; 0 cm for front/back necklines

Attention! First of all, please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches. They must match up with corresponding pieces.



CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Fabric:

1. Back– cut 1
2. Front – cut 1
3. Placket (casing) – cut 2

*Cut fabric for ties of necessary length and 10 cm width, and bias strip for finishing neckline.

INSTRUCTIONS:

1. Sew right shoulder seam. Serge and press seam toward back.
2. Cut a bias strip 4 cm width and of length equal to front/back neckline length. Fold the strip along the center right side out. Lay it flat and press long edges to marked middle line. Finish neckline with the bias strip.
3. Sew left shoulder seam. Serge and press seam toward back.
4. Serge lower edge, press onto wrong side, and topstitch.
5. Press plackets (casings) short edges onto wrong side and topstitch. Press plackets long edges onto wrong side. Pin the plackets (casings) on wrong side of front and back as marked and topstitch at 0.1 cm from the fold.
6. Cut 2 ties of necessary length and 10 cm width. Fold ties along the center, wrong side out, then sew along one long/one short side. Turn ties right side out, press. Fold raw allowances under and topstitch at 0.1 cm from edges. Insert ties into casings.

TECHNICAL DRAWING:

