

Sewing Pattern — Blouse 5689

Recommendations on fabric: natural/mixed fabrics (silk).

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: 1 cm for all seams, 2 cm for the garment.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Back part – 1 piece
2. Front part – 1 piece
3. Back sleeve – 2 pieces
4. Front sleeve – 2 pieces
5. Front detail – 1 piece
6. Back facing – 1 piece
7. Front facing – 1 piece

INSTRUCTIONS:

1. Stitch side edges excluding a slit for closure in left side edge. Press right side seam backward pressing, press left side seam apart pressing closure slit. Neaten seams.
2. Stitch the zipper into left side seam.
3. Stitch garment shoulder edges, press seams and neaten them.
4. Stitch facings' shoulder seams and press them apart.

5. Fold front detail along the center right side out. Lay the facing on the blouse right sides together, insert front detail between them and overstretch. Slash seam's roundings, fold the facing into wrong side and press it.
6. Slash armholes at notches. Cut a piping of 4 cm width and of length equal to armhole lower part's length. Press the piping long the center right side out. Lay the piping on armhole lower part right sides together, then overstretch. Fold the piping into wrong side. Topstitch seam allowance on the piping with the seam of 0.1 cm width.
7. Press sleeve upper edge into wrong side and topstitch it. Stitch sleeves into armhole upper part. Neaten seams.
8. Neaten garment/sleeve hems, fold into wrong side and topstitch.

TECHNICAL DRAWING:

