

## Sewing Pattern — Blouse 5688

Recommendations on fabric: sheer natural/mixed fabric

You will also need: fusing; bride of 7 cm long

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: 1 cm for all seams.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



### **CUTTING:**

Main fabric:

1. Back part – 1 piece
2. Front part – 1 piece
3. Waistband – 2 pieces
4. Sleeve facing – 2 pieces
5. Back neckline facing – 1 piece
6. Front neckline facing – 1 piece

### **INSTRUCTIONS:**

1. Apply the fusing to wrong side of front/back neckline facings as well as of sleeve facings.
2. Stitch sleeve upper edges. Press sleeve upper seams backward and neaten them.
3. Stitch side edges and sleeve lower edges with the same stitch folding details wrong side out.
4. Stitch neckline facing's shoulder edges, press seams apart. Lay facing's right side on blouse wrong side and overstitch the neckline. Slash allowances at roundings, turn the facing into right side, fold lower edge under and topstitch the facing on the blouse with 0.1 cm stitch.

5. Stitch sleeve facings' edges, press seams apart. Lay facing's right side on sleeve's wrong side and overstretch sleeve hem. Slash allowances at roundings, turn the facing into right side, fold lower edge under and topstitch the facing on the blouse with 0.1 cm stitch.
6. Slash blouse hem at notches. Neaten a segment between marks. Fold neaten edge into wrong side and lay the bride under it. Stretch the bride and topstitch with zig zags leaving 1 cm ends.
7. Lay waistbands right sides together and overstretch along three edges: between the notch and side edge, side and lower edge. Turn the detail right side out and press it.
8. Stitch outer waistband to blouse hem catching bride end into the seam. Fold the raw allowance under and topstitch along the seam joining the waistband.

**TECHNICAL DRAWING:**

