

## Sewing Pattern — Skirt 5683

Recommendations on fabric: sheer natural/mixed silk .

You will also need: fusing, concealed zip

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: 1 cm for all seams, 2 cm for the hem

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



### **CUTTING:**

Fabric:

1. Back yoke – 1 piece
2. Front yoke – 1 piece
3. Back facing – 1 piece
4. Front facing – 1 piece
5. Upper flounce – 1 piece
6. Middle flounce – 1 piece
7. Lower flounce – 1 piece

Fusing: front/back facings.

### **INSTRUCTIONS:**

1. Apply the fusing to wrong side of facings.
2. Stitch darts into back yoke and press them toward the center.
3. Stitch left side edge between closure mark and the hem. Press the seam apart pressing slit allowances, then neaten it. Lay the zipper under slit allowances and stitch it with its teeth invisible.
4. Stitch right side seam and neaten it. Press the seam backward.

5. Stitch side edges of facings, press seams apart. Neaten lower edge. Lay the facing on skirt upper edge right sides together, then overstretch. Topstitch overstretching on facings at 0.2 cm from overstretching. Fold facings into wrong side and press them.
6. Stitch flounce edges together. Press seams leftward and neaten them.
7. Make loose stitches along upper flounce's upper edge. Pull the edge to make it equal to yokes lower edges length, arranging pleats evenly. Stitch upper flounce to yokes. Press the seam upward and neaten it.
8. Make loose stitches along middle flounce's upper edge. Pull the edge to make it equal to upper flounce lower edge's length, arranging pleats evenly. Stitch middle flounce to upper flounce. Press the seam upward and neaten it.
9. Make loose stitches along lower flounce's upper edge. Pull the edge to make it equal to middle flounce lower edge's length, arranging pleats evenly. Stitch lower flounce to middle flounce. Press the seam upward and neaten it.
10. Press the hem into wrong side, fold it under and topstitch.

**TECHNICAL DRAWING:**

