

Sewing Pattern — Skirt 5681

Recommendations on fabric: bottom-weight natural/mixed fibers.

You will also need: fusible interfacing, invisible zipper

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam allowance: all seams – on hem – 2 cm; 1 cm on all other seams

Attention! First of all, please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches. They must match up with corresponding pieces.



CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Fabric:

1. Upper skirt – cut 2
2. Middle skirt – cut 2
3. Side skirt – cut 2
4. Inset – cut 2
5. Facing – cut 2

Fusible interfacing: facing

INSTRUCTIONS:

1. Apply the interfacing to wrong side of facings.
2. Sew inset to side skirt. Serge, press seam toward inset, and topstitch.
3. Sew upper skirt to middle skirt. Serge, press seam upward, and topstitch.
4. Sew middle skirt to side skirt. Serge, press seam toward middle skirt, and topstitch.
5. Repeat steps 2-4 for back skirt.
6. Serge left side edges separately. Sew left side seam from zipper mark to hem. Press seam apart, including opening for zipper. Sew in zipper.
7. Sew right side seam, serge and press seam toward back.

8. Sew facing side seam and press the seam apart. Serge lower edge. Pin facing on skirt upper edge, right sides together, then sew. Clip into curves and understitch. Fold facings onto wrong side and press. Fold short edges of facing under and slipstitch to zipper tape. Tack facing at seams.
9. Serge lower edge of garment, turn onto wrong side, and topstitch.

TECHNICAL DRAWING:

