

Sewing Pattern — Jacket 4242

Recommended fabric: natural or mixed suiting fabrics.

You will also need: fusible interfacing; lining; 5 buttons; shoulder pads; sleeve heads.

If the pattern has a double line around it, the seam allowances are included.

Seam allowance: all seams - 1 cm, hem of sleeve - 3.5 cm.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.



Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches, they must coincide.

CUTTING:

(On the pattern pieces, “beam” means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.)

Darts: The fold of the dart is always pressed toward the center of your garment, or down toward the hem.

Main fabric:

1. Center back— cut 2
2. Side back – cut 2
3. Side front – cut 2
4. Center right front _1 – cut 1
5. Center right front _2 – cut 1
6. Center right front _3 – cut 1
7. Center left front – cut 1
8. Collar - cut 2
9. Left buttonstand - cut 1
10. Right buttonstand_1 – cut 1
11. Right buttonstand_2 – cut 1
12. Right buttonstand_3 – cut 1
13. Back neckline facing – cut 1
14. Bottom facing of back – cut
15. Upper sleeve - cut 2
16. Lower sleeve – cut 2

Lining:

1. Front – cut 2
2. Side front - cut 2
3. Center back – cut 2
4. Side back – cut 2
5. Upper sleeve - cut 2
6. Lower sleeve – cut 2

Lining of central back, side back, and front parts are cut using main pattern pieces except for the width of neckline facing, hem and buttonstand facing.

Fusible interfacing:

1. Center right front _1 – cut 1
2. Center right front _2 – cut 1
3. Center right front _3 – cut 1
4. Center left front - cut 1
5. Collar - cut 1
6. Left buttonstand - cut 1
7. Right buttonstand_1 – cut 1
8. Right buttonstand_2 - cut 1
9. Right buttonstand_3 – cut 1
10. Back neckline facing – cut 1
11. Bottom facing of back part – cut 1

INSTRUCTIONS:

1. Apply fusible interfacing.
2. Sew and press darts on back towards center. Sew side backs to center backs; clip into curves, press princess seams open. Sew center back seam, press seam open.
3. Sew dart on center left front, press toward hem. Sew side front to left front, press seam allowances to side edge.
4. Pin center front _1 with central front _2, right sides together, and sew from buttonstand edge up to the buttonhole beginning, and from buttonhole end up to the edge of the armhole. Press seam open. Pin center front _2 with center front _3, right sides together, and sew from buttonstand edge up to the buttonhole beginning, and from buttonhole end up to the edge of the armhole. Press seam open. Sew right front side to right front, press seam allowances to side edge.
5. Sew shoulder and side edges of the jacket, press seams open.
6. Pin collars right sides together and sew outer edge. Clip into curves and turn collar out, straighten and press. Sew collar into the neckline of the jacket, tack ends of collar to buttonstand edge.
7. Pin right buttonstand_1 with right buttonstand_2, right sides together, and sew from buttonstand edge up to buttonhole beginning and from buttonhole end up to inner edge. Press open seam. Pin right buttonstand_2, with right buttonstand_3, right sides together and sew from buttonstand edge up to buttonhole beginning and from buttonhole end up to inner edge. Press seam open.
8. Sew shoulder seams and press seams open. Sew back neck facing and buttonstand neckline facing together. Press seam open.
9. Lay buttonstand and facings onto right side of front, right side downwards, pin together and sew buttonstand, the neckline of front, the neckline of back and hem of the jacket. Clip into curves and trim corners. Press seams toward facings and understitch. Turn, press and topstitch.
10. Sew elbow sleeve seam, press open. Sew front sleeve seam, press open.
11. Sew a gathering stitch along sleeve cap to adjust ease. Sew sleeves into armholes according to notches, adjusting ease. Sew in shoulder pads and sleeve heads.
12. Sew seams on lining pieces and sew in sleeves, leaving an opening in front right seam of sleeve for turning. Sew lining to inner buttonstand edges and to facings. Press apart allowances of

collar connecting seams and tack close to seams. Sew lining to hem of sleeve. Turn jacket through the opening in sleeve. Slipstitch opening closed.

13. Make buttonholes on right front; sew buttons on left front.

TECHNICAL DRAWING:

