

Sewing Pattern — Blouse 5675

Recommendations on fabric: medium/high stretch- jersey (natural or mixed) needs to look the same on both sides of fabric

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam allowance: 1.5 cm for the hem/sleeve hems; 1 cm for other seams

Attention! First of all, please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches. They must match up with corresponding pieces.



CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Advice:

Knit fabric pieces are sewn together with special stretch-stitch or narrow zig-zag stitch. Seam allowance on hem is stitched with twin needles to save stretchiness. Pieces can also be sewn together with 3 or 4 – thread serger. When serging, cut seam allowances to 0.6 – 0.8 cm.

Fabric:

1. Back – cut 1
2. Front – cut 1
3. Front yoke – cut 1
4. Sleeve – cut 2

INSTRUCTIONS:

1. Sew back right shoulder to front yoke, right sides together. Serge and press toward back.
2. Make 1 twist on the yoke and sew left shoulder to back. Serge and press toward toward back.
3. Make a snip into front yoke at the mark on the neckline. Serge the neckline. On the yoke, serge the segment between the notch and shoulder seam. Press allowances onto wrong side and topstitch.
4. Snip seam allowance on front at upper edge mark. Serge segment between

notches, press onto wrong side, then topstitch.

5. Sew front to the yoke between the notch and armholes. Serge the seam and press it.

6. Sew side seams. Serge and press seam toward back.

7. Sew sleeve seams. Serge and press toward back.

8. Sew sleeves into armholes matching notches. Serge seam and press.

9. Serge lower edge of garment and sleeve edges. Turn onto wrong side, press, and topstitch or use coverstitch.

TECHNICAL DRAWING:

