

Sewing Pattern — Blouse 5669

Recommendations on fabric: middle/high stretchable jersey (natural or mixed)

You will also need: jersey braid (or piping) for trimming

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Seam allowance: 1.5 cm for the hem/sleeve hems, 0 cm for the neck/strap's side edges, 1 cm for other seams

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Main fabric:

1. Right back part – 1 piece
2. Left back part – 1 piece
3. Right front part – 1 piece
4. Left front part – 1 piece
5. Right sleeve- 1 piece
6. Left sleeve – 1 piece

Our advice: stitch jersey details with special elastic/zig-zag stitches. If you use an overlock, cut seam allowances till 0.6-0.8 cm width. Topstitch hem allowances with double needle to save elasticity.

INSTRUCTIONS:

1. Stitch front parts together. Stitch back parts together. Neaten seams and press them.
2. Stitch straps along shoulder edge as follows: stitch right front part to left back part, stitch right back part to left front part. Stitch right shoulder edge. Neaten seams and press them backwards.
3. Trim straps' edges/neckline with the piping. Begin trimming at left armhole.
4. Stitch side front/side back edges. Neaten seams and press them backwards.
5. Neaten left sleeve's upper edge. Press it into wrong side and topstitch.

6. Stitch sleeve seams. Neaten seams and press them.
7. Stitch sleeves into armholes coinciding notches. Neaten seams and press them.
8. Neaten the hem and sleeve hems. Press them into wrong side and topstitch.
9. Stitch the collar as a ring. Press the collar along the center right side out. Stitch outer collar to front/yoke necklines coinciding notches. Collar seam goes at left shoulder point. Fold collar allowances in and stitch them together.

TECHNICAL DRAWING:

