

Sewing Pattern — Top 5662

Recommendations on fabric: middle/high stretchable jersey (natural or mixed).

You will also need: decorative ring for a strap, jersey braid (or the piping) to trim.

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Seam allowance: 1.5 cm for the hem and upper back edge, 0 cm for front armhole, 1 cm for other seams

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Back part – 1 piece
2. Front part – 1 piece

OUR ADVICE: stitch jersey details with special elastic/zig-zag stitches. If you use an overlock, cut seam allowances till 0.6-0.8 cm width. Topstitch hem allowances with double needle to save elasticity.

INSTRUCTIONS:

1. Neaten upper front edges, press into wrong side and topstitch them.
2. Cut the facing of front oval edge depending on ring's width. **How to count the facing:** ring's width + 0.5 cm for free wearing + 2 cm for seams = facing's width.
3. Neaten facing's outer/side edges. Fold facing's side edges into wrong side at 0.7 cm width. Lay the facing on the front part right sides together and overstretch along inner edge. Roll the facing into wrong side inserts the ring between the front part and facings then topstitch.

4. Trim front armhole with jersey braids leaving braid's ends on the strap.
5. Neaten upper back edge.
6. Stitch side front/side back edges. **NB:** back side seam is 1.5 cm longer than front side seam. Make edges equal beginning from lower edge. Neaten seams and press them backward.
7. Fold back upper allowance into wrong side and topstitch it.
8. Neaten the hem. Press it into wrong side and topstitch.
9. Adjust strap's length when trying on. Sew straps' ends to back upper edge.

TECHNICAL DRAWING:

