

Sewing Pattern — Top 5660

Recommendations on fabric: middle/high stretchable jersey (natural or mixed)

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: 1.5 cm for the hem, 1 cm for other seams

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Back part – 1 piece
2. Front part – 1 piece
3. Placket – 1 piece

OUR ADVICE: stitch jersey details with special elastic/zig-zag stitches. If you use an overlock, cut seam allowances till 0.6-0.8 cm width. Topstitch hem allowances with double needle to save elasticity

INSTRUCTIONS:

1. Stitch side front/side back edges. Neaten the seams and press them backward.
2. Neaten the hem and armhole edge. Fold them into wrong side, press and topstitch them.
3. Stitch the placket forming a ring. Press the placket along the center right side out.
4. Stitch outer placket to back/front parts coinciding notches. Fold inner placket's allowances into wrong side and topstitch along the seam.
4. Neaten facing's outer/inner edges. Fold facing's side edges into wrong side at 0.7 cm width. Lay the facing on the front part right sides together and overstitch along inner edge. Fold the facing into wrong side, insert the ring between the front part and the facing, and then topstitch.
5. Fold the strap along the center wrong side out. Overstitch its' long edge. Turn the strap right side out and press it. Neaten open edges together. Pull straps one edge through the ring and fix it on wrong side. Cross straps on the back, adjust the length and sew the straps to back upper edge.

TECHNICAL DRAWING:

